

HV RAD-LDD Mil X7R HV 49467, Ceramic, 1000 pF, 10%, 1000 VDC, X7R, Radial Leaded Multilayer Ceramic Capacitor, Lead Spacing = 5.59mm



General Information	
Series:	HV RAD-LDD Mil X7R HV 49467
Style:	Radial
Description:	Radial Leaded Multilayer Ceramic Capacitor
RoHS:	No
Prop 65:	WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov .
Termination:	Copper
AEC-Q200:	No

Dimensions	
L	8.13mm NOM
H	7.11mm
T	6.35mm NOM
S	5.59mm +/-0.762mm
LL	3.175mm NOM
F	0.635mm +0.102/-0.051mm

Specifications	
Capacitance:	1000 pF
Capacitance Tolerance:	10%
Voltage DC:	1000 VDC
Dielectric Withstanding Voltage:	1200 VDC
Temperature Range:	-55/+125°C
Temperature Coefficient:	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	30 ppm/C
Dissipation Factor:	2.5%
Aging Rate:	2% Loss/Decade Hour
Insulation Resistance:	100 GOhms

Packaging Specifications	
Packaging Quantity:	28

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)