


## T493C106M035CH6410

T493 HRA, Tantalum, MnO2 Tantalum, HRA, 10 uF, 20%, 35 VDC, SMD, MnO2, Molded, High Reliability, C (0.01%/1000 Hrs), 2 Ohms, 6032, Height Max = 2 8mm



	Click	here	for	the	3D	mode
--	-------	------	-----	-----	----	------

Dimensions	
Footprint	6032
L	6mm +/-0.3mm
W	3.2mm +/-0.3mm
Н	2.5mm +/-0.3mm
Т	0.13mm REF
S	1.3mm +/-0.3mm
F	2.2mm +/-0.1mm
A	3.1mm MIN
В	0.5mm +/-0.15mm
E	2.4mm REF
G	2.8mm REF
Р	0.5mm MIN
R	1mm REF
X	0.1mm +/-0.1mm

Packaging Specifications			
Packaging	T&R, 178mm		
Packaging Quantity	500		

General Information				
Series	T493 HRA			
Dielectric	MnO2 Tantalum			
Style	SMD Chip			
Description	SMD, MnO2, Molded, High Reliability			
Features	High Reliability			
RoHS	No			
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.			
Termination	Solder Coated			
AEC-Q200	No			
Component Weight	224.2 mg			
Notes	P and R dimensions represents the minimum solderable area of the termination surface entirely below cutout (if one is present).			

10 uF
20%
35 VDC (85C), 23.45 VDC (125C)
-55/+125°C
85°C
6% 120Hz 25C
C (0.01%/1000 Hrs)
2 Ohms (100kHz 25C)
3.5 uA (5min 25°C)
10 Cycles Surge Current Testing At -55C And +85C Before Weibull

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)