



Click [here](#) for the 3D model.

### Dimensions

|    |                    |
|----|--------------------|
| L  | 41.5mm +0.3/-0.7mm |
| H  | 45mm +0.1/-0.7mm   |
| T  | 30mm +0.3/-0.7mm   |
| S  | 37.5mm +/-0.4mm    |
| LL | 25mm +2/-1mm       |
| F  | 1mm +/-0.05mm      |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Tray |
| Packaging Quantity | 60   |

### General Information

|                  |                          |
|------------------|--------------------------|
| Series           | R49                      |
| Dielectric       | Metallized Polypropylene |
| Style            | Radial                   |
| Features         | EMI Safety               |
| RoHS             | Yes                      |
| Lead             | Wire Leads               |
| Safety Class     | X1                       |
| Qualifications   | ENEC, UL, cUL            |
| AEC-Q200         | No                       |
| THB Performance  | No                       |
| Component Weight | 68.69 g                  |

### Specifications

|                       |              |
|-----------------------|--------------|
| Capacitance           | 6.8 uF       |
| Capacitance Tolerance | 10%          |
| Voltage AC            | 330 VAC (X1) |
| Voltage DC            | 800 VDC      |
| Temperature Range     | -40/+110°C   |
| Rated Temperature     | 110°C        |
| Dissipation Factor    | 0.1% 1kHz    |
| Insulation Resistance | 4.4118 GOhms |
| Max dV/dt             | 100 V/us     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)