


T513X226K035CC6310

T513 HRA, Tantalum, MnO2 Tantalum, HRA Multi-Anode, 22 uF, 10%, 35 VDC, SMD, MnO2, Molded, Military Equivalent, MAT High Reliability, C (0.01%/1000 Hrs), 100 mOhms, 7343, Height Max = 4.3mm



Click here for the 3D model.

Dimensions	
Footprint	7343
L	7.3mm +/-0.3mm
W	4.3mm +/-0.3mm
Н	4mm +/-0.3mm
Т	0.13mm REF
S	1.3mm +/-0.3mm
F	2.4mm +/-0.1mm
Α	3.8mm MIN
В	0.5mm +/-0.15mm
E	3.5mm REF
G	3.5mm REF
Р	1.7mm REF
R	1mm REF
X	0.1mm +/-0.1mm

Packaging Specifications	
Packaging	T&R, 178mm
Packaging Quantity	500

General Informatio	n ,
Series	T513 HRA
Dielectric	MnO2 Tantalum
Style	SMD Chip
Description	SMD, MnO2, Molded, Military Equivalent, MAT High Reliability
Features	Low ESR
RoHS	No
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
SCIP Number	ff0ac6de-04a5-49fb-9ad1-557da7f701ca
Termination	Hot Solder Dipped
AEC-Q200	No
Component Weight	430.15 mg

Capacitance 22 uF Capacitance Tolerance 10% Voltage DC 35 VDC (85C), 23.45 VDC (125C) Temperature Range -55/+125°C Rated Temperature 85°C Dissipation Factor 6% 120Hz 25C Failure Rate C (0.01%/1000 Hrs) Resistance 100 mOhms (100kHz 25C)	Specifications	
Tolerance 10% Voltage DC 35 VDC (85C), 23.45 VDC (125C) Temperature Range -55/+125°C Rated Temperature 85°C Dissipation Factor 6% 120Hz 25C Failure Rate C (0.01%/1000 Hrs) Resistance 100 mOhms (100kHz 25C)	Capacitance	22 uF
Temperature Range Rated Temperature Dissipation Factor Failure Rate C (0.01%/1000 Hrs) Resistance 7-55/+125°C 85°C 6% 120Hz 25C Failure Rate C (0.01%/1000 Hrs)		10%
Range Rated Temperature Dissipation Factor Failure Rate C (0.01%/1000 Hrs) Resistance C (0.00 MOhms (100kHz 25C)	Voltage DC	35 VDC (85C), 23.45 VDC (125C)
Temperature Dissipation Factor 6% 120Hz 25C Failure Rate C (0.01%/1000 Hrs) Resistance 100 mOhms (100kHz 25C)		-55/+125°C
Failure Rate C (0.01%/1000 Hrs) Resistance 100 mOhms (100kHz 25C)		85°C
Resistance 100 mOhms (100kHz 25C)	Dissipation Factor	6% 120Hz 25C
	Failure Rate	C (0.01%/1000 Hrs)
	Resistance	100 mOhms (100kHz 25C)
Leakage Current 7.7 uA (5min 25°C)	Leakage Current	7.7 uA (5min 25°C)
Testing and 10 Cycles Surge Current Testing At -55C And Reliability +85C After Weibull	3	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)