


HP08CN104GN

Aliases (HP08CN104G)

HP LDD Indust COG HT200C, Ceramic, 0.1 uF, 2%, 100 VDC, COG, Commercial, High Temperature, Lead Spacing = 10.16mm



General Information		
Series	HP LDD Indust COG HT200C	
Style	Radial	
Description	Commercial, High Temperature	
Features	LDD High Temperature 200C	
RoHS	No	
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
Termination	Nickel	
Failure Rate	N/A	
AEC-Q200	No	

Specifications			
Capacitance	0.1 uF		
Capacitance Tolerance	2%		
Voltage DC	100 VDC		
Dielectric Withstanding Voltage	250 VDC		
Temperature Range	-55/+200°C		
Temperature Coefficient	COG		
Dissipation Factor	0.15%		
Insulation Resistance	10 GOhms		

Dimensions	
L	12.7mm MAX
Н	12.7mm MAX
Т	6.35mm MAX
S	10.16mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications	
Packaging	Waffle, Tray
Packaging Quantity	1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)