

10HV14N102JN

Aliases (10HV14N102J)

HV RAD-LDD Indust COG HVHT200C, Ceramic, 1000 pF, 5%, 1000 VDC, COG, Commercial, High Temperature, HighVoltage, Lead Spacing = 12.7mm



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-------------------------|
| L | 15.75mm MAX |
| H | 12.7mm MAX |
| T | 7.62mm MAX |
| S | 12.7mm +/-0.762mm |
| LL | 3.175mm MIN |
| F | 0.635mm +0.102/-0.051mm |

| Packaging Specifications | |
|--------------------------|--------|
| Packaging | Waffle |
| Packaging Quantity | 20 |

| General Information | |
|---------------------|---|
| Series | HV RAD-LDD Indust COG HVHT200C |
| Style | Radial |
| Description | Commercial, High Temperature, HighVoltage |
| Features | Commercial |
| RoHS | With Exemptions |
| REACH | SVHC (Pb - CAS 7439-92-1) |
| SCIP Number | ef26097b-3862-4ee0-b0ad-404a563ece0f |
| Termination | Nickel |
| Failure Rate | N/A |
| AEC-Q200 | No |

| Specifications | |
|---------------------------------|---------------------|
| Capacitance | 1000 pF |
| Capacitance Tolerance | 5% |
| Voltage DC | 1000 VDC |
| Dielectric Withstanding Voltage | 1500 VDC |
| Temperature Range | -55/+200°C |
| Temperature Coefficient | COG |
| Dissipation Factor | 0.15% |
| Aging Rate | 0% Loss/Decade Hour |
| Insulation Resistance | 100 GOHms |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)