



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-----------------|
| L | 26mm MAX |
| H | 16.5mm MAX |
| T | 7mm MAX |
| S | 22.5mm +/-0.4mm |
| LL | 6mm NOM |
| F | 0.8mm NOM |

Packaging Specifications

| | |
|--------------------|------|
| Packaging | Tray |
| Packaging Quantity | 216 |

General Information

| | |
|------------|--|
| Series | PHE426/F426 |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Notes | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

Specifications

| | |
|-----------------------|--------------------------|
| Capacitance | 0.056 uF |
| Capacitance Tolerance | 5% |
| Voltage AC | 250 VAC |
| Voltage DC | 1000 VDC, 740 VDC (105C) |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.05% 1kHz, 0.25% 100kHz |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 300 V/us |
| Inductance | 6 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)