
KEMET Part Number: HP06AB224JN

(HP06AW224JN)



HP LDD Indust X7R HT200C, Ceramic, 0.22 uF, 5%, 25 VDC, X7R, High Temperature, Lead Spacing = 5.08mm



Dimensions		
L	7.62mm MAX	
Н	7.62mm MAX	
Т	3.81mm MAX	
S	5.08mm +/-0.762mm	
LL	3.175mm MIN	
F	0.635mm +0.102/-0.051mm	

Packaging Specifications		
Packaging:	Waffle, Tray	
Packaging Quantity:	28	

General Information	
Series:	HP LDD Indust X7R HT200C
Style:	Radial
Description:	High Temperature
Features:	LDD High Temperature 200C
RoHS:	No
Prop 65:	WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov.
Termination:	Nickel
Failure Rate:	N/A
AEC-Q200:	No

Specifications	
Capacitance:	0.22 uF
Measurement Condition:	1 kHz 1.0Vrms
Capacitance Tolerance:	5%
Voltage DC:	25 VDC
Dielectric Withstanding Voltage:	62.5 VDC
Temperature Range:	-55/+200°C
Temperature Coefficient:	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	+15%/-40%, 1kHz 1.0Vrms
Dissipation Factor:	2% 1 kHz 1.0Vrms
Insulation Resistance:	4.55 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)