



Click [here](#) for the 3D model.

### Dimensions

|    |                    |
|----|--------------------|
| L  | 26.5mm +0.3/-0.5mm |
| H  | 22mm +0.1/-0.5mm   |
| T  | 13mm +0.2/-0.5mm   |
| S  | 22.5mm +/-0.4mm    |
| LL | 4mm +0.5mm         |
| F  | 0.8mm +/-0.05mm    |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 300       |

### General Information

|                  |                              |
|------------------|------------------------------|
| Series           | R52 310 VAC MINI             |
| Dielectric       | Metallized Polypropylene     |
| Style            | Radial                       |
| Features         | EMI Safety                   |
| RoHS             | Yes                          |
| Lead             | Wire Leads                   |
| Safety Class     | X2                           |
| Qualifications   | ENEC, UL, cUL, CQC, AEC-Q200 |
| AEC-Q200         | Yes                          |
| THB Performance  | Yes                          |
| Component Weight | 9.63 g                       |

### Specifications

|                       |              |
|-----------------------|--------------|
| Capacitance           | 2.2 uF       |
| Capacitance Tolerance | 20%          |
| Voltage AC            | 310 VAC (X2) |
| Voltage DC            | 630 VDC      |
| Temperature Range     | -40/+110°C   |
| Rated Temperature     | 110°C        |
| Dissipation Factor    | 0.2% 1KHz    |
| Insulation Resistance | 66 GOhms     |
| Max dV/dt             | 200 V/us     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)