


ESG227M250AN3AA

ESG, Aluminum Electrolytic, 220 uF, 20%, 250 VDC, -40/+105°C, Lead Spacing = 7.5mm



TERMINAL END VIEW



Click here for the 3D model.

Dimensions	
D	18mm +/-0.5mm
L	40mm +2mm
S	7.5mm +/-0.5mm
LL Negative	15mm MIN
LL Positive	20mm MIN
F	0.8mm NOM

Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	500

General Information		
Series	ESG	
Dielectric	Aluminum Electrolytic	
Description	Long Life Single Ended Aluminum Electrolytic	
Features	Long Life	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	

Specifications		
Capacitance	220 uF	
Capacitance Tolerance	20%	
Voltage DC	250 VDC, 300 VDC (Surge)	
Temperature Range	-40/+105°C	
Rated Temperature	105°C	
Life	5000 Hrs	
Dissipation Factor	15% 120Hz 20C	
Ripple Current	820 mAmps (120Hz 105C)	
Leakage Current	3310 uA (2min 20°C)	
Impedance Ratio at -25C	3	
Impedance Ratio at -40C	6	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)