



The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

### General Information

|                  |                           |
|------------------|---------------------------|
| Series           | C900AC SFTY X1-400 Y2-250 |
| Style            | Radial Disc               |
| RoHS             | Yes                       |
| Termination      | Tin                       |
| Failure Rate     | N/A                       |
| Qualifications   | UL, ENEC, VDE, CSA, CAN   |
| AEC-Q200         | No                        |
| Halogen Free     | Yes                       |
| Component Weight | 500 mg                    |

### Specifications

|                                 |                            |
|---------------------------------|----------------------------|
| Capacitance                     | 100 pF                     |
| Capacitance Tolerance           | 5%                         |
| Voltage AC                      | 400 VAC (X1), 250 VAC (Y2) |
| Dielectric Withstanding Voltage | 2600 VDC                   |
| Temperature Range               | -40/+125°C                 |
| Temperature Coefficient         | SL                         |
| Insulation Resistance           | 10 GOhms                   |
| Quality Factor                  | 1000                       |
| Safety Class                    | X1/Y2                      |

Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| D  | 10mm MAX        |
| T  | 5mm MAX         |
| S  | 7.5mm +/-1mm    |
| LL | 4mm +/-1mm      |
| F  | 0.55mm +/-0.1mm |
| G  | 3mm MAX         |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 500       |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)