
## **KEMET Part Number: C0805C471J5RALTM**

(C0805C471J5RAL7025)



SMD Comm X7R SnPb, Ceramic, 470 pF, 5%, 50 VDC, X7R, SMD, MLCC, Temperature Stable, SnPb Termination, 0805



| Dimensions |                  |  |
|------------|------------------|--|
| Chip Size  | 0805             |  |
| L          | 2mm +/-0.2mm     |  |
| W          | 1.25mm +/-0.2mm  |  |
| Т          | 0.78mm +/-0.10mm |  |
| S          | 0.75mm MIN       |  |
| В          | 0.5mm +/-0.25mm  |  |

| Packaging Specifications |                        |  |
|--------------------------|------------------------|--|
| Packaging:               | T&R, 180mm, Paper Tape |  |
| Packaging Quantity:      | 4000                   |  |

| General Information |   |  |
|---------------------|---|--|
| Series:             | SMD Comm X7R SnPb   |  |
| Style:              | SMD Chip  |  |
| Description:        | SMD, MLCC, Temperature<br>Stable, SnPb Termination                                  |  |
| Features:           | SnPb Termination  |  |
| RoHS:               | No  |  |
| Prop 65:            | warning: Cancer and reproductive harm - www.p65warnings.ca.gov. 5549986b-60cf-4a2a- |  |
| SCIP Number:        | afbb-4ad1d7a11dcb   |  |
| Termination:        | Lead (SnPb)   |  |
| Marking:            | Yes   |  |
| AEC-Q200:           | No  |  |
| Component Weight:   | 11 mg   |  |
| Shelf Life:         | 78 Weeks  |  |
| MSL:                | 1   |  |

| Specifications  |  |  |
|---|--|--|
| Capacitance:  | 470 pF   |  |
| Measurement Condition:  | 1 kHz 1.0Vrms                                      |  |
| Capacitance Tolerance:  | 5%   |  |
| Voltage DC:   | 50 VDC   |  |
| Dielectric Withstanding<br>Voltage:                                 | 125 VDC  |  |
| Temperature Range:  | -55/+125°C   |  |
| Temperature Coefficient:  | X7R  |  |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC): | 15%, 1kHz 1.0Vrms                                  |  |
| Dissipation Factor:   | 2.5% 1 kHz 1.0Vrms                                 |  |
| Aging Rate:   | 3% Loss/Decade Hour: Referee<br>Time is 1000 Hours |  |
| Insulation Resistance:  | 100 GOhms  |  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)