



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-------------------|
| D | 8.92mm +/-0.25mm |
| L | 19.96mm +/-0.79mm |
| L2 | 23.42mm |
| LL | 38.1mm +/-6.35mm |
| F | 0.64mm +/-0.05mm |
| G | 2.67mm +/-0.79mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 20 |

General Information

| | |
|----------------|--|
| Series | T240 |
| Dielectric | MnO2 Tantalum |
| Style | Axial Hermetic |
| Description | Axial, Solid Tantalum, Hermetically Sealed, Military, High Reliability |
| Features | Extended Capacitance, Low Leakage, Low DF, High Reliability |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov |
| SCIP Number | bee1eed4-5fec-4214-9f43-620c5b22071f |
| Termination | Lead (SnPb) |
| Lead | Wire Leads |
| Qualifications | GR500 |
| AEC-Q200 | No |
| Construction | Hermetic |
| Notes | Dimensions Include Insulating Sleeve. When supplied on T&R or AMMO, lead length is determined by taping specification. |

Specifications

| | |
|-----------------------|--|
| Capacitance | 560 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 10 VDC (85C), 9 VDC (125C Surge), 0.1 VDC (125C Reverse) |
| Temperature Range | -55/+125°C |
| Dissipation Factor | 8% |
| Failure Rate | P (0.1%/1000 Hrs) |
| Resistance | 0.06 Ohms (100kHz) |
| Leakage Current | 4 uA |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)