



Click [here](#) for the 3D model.

Dimensions

D	136mm +2mm
L	282mm +/-2mm
L1	285mm +/-2mm
S	50mm +/-0.3mm
D1	139mm +0.5mm

Packaging Specifications

Mounting	Bolt - M12x16
Packaging	Bulk, Bag
Packaging Quantity	2

General Information

Series	C44U-M
Dielectric	Metallized Polypropylene
Style	Can
Features	DC Filtering, Energy Storage
RoHS	With Exemptions
REACH	SVHC (Pb - CAS 7439-92-1)
Lead	Screw Terminals M6
AEC-Q200	No
Component Weight	4400 g
Miscellaneous	Thermal Resistance = 1.6 C/W. Weight = 10100 grams.

Specifications

Capacitance	3400 uF
Capacitance Tolerance	10%
Voltage DC	900 VDC
Temperature Range	-40/+85°C
Rated Temperature	75°C
Insulation Resistance	10 MOhms
Max dV/dt	4 V/us
Resistance	1.16 mOhms (1kHz)
Ripple Current	100 Amps (1kHz 40C), 13200 Amps (Peak)
Inductance	85 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)