


C0805X473K1RAC3316

SMD Auto X7R VW80808, Ceramic, 0.047 uF, 10%, 100 VDC, X7R, SMD, MLCC, Automotive Grade, 0805



Click here for the 3D model.

Dimensions	
Chip Size	0805
L	2mm +/-0.3mm
W	1.25mm +/-0.3mm
Т	1.25mm +/-0.15mm
S	0.75mm MIN
В	0.5mm +/-0.25mm

## **Packaging Specifications**

Packaging Packaging Quantity

T&R, 180mm, Plastic Tape 2500

General Information	
Series	SMD Auto X7R VW80808
Style	SMD Chip
Description	SMD, MLCC, Automotive Grade
Features	VW 80808 Specification Compliant
RoHS	Yes
Termination	Flexible Termination
Failure Rate	N/A
Qualifications	AEC-Q200
AEC-Q200	Yes
Shelf Life	152 Weeks

Specifications		
Capacitance	0.047 uF	
Capacitance Tolerance	10%	
Voltage DC	100 VDC	
Dielectric Withstanding Voltage	250 VDC	
Temperature Range	-55/+125°C	
Temperature Coefficient	X7R	
Dissipation Factor	2.5% 120 Hz 25C	
Insulation Resistance	21.2766 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)