



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| L | 41mm MAX |
| H | 24mm MAX |
| T | 13mm MAX |
| S | 37.5mm +/-0.5mm |
| LL | 6mm NOM |
| F | 1mm NOM |

| Packaging Specifications | |
|--------------------------|------|
| Packaging | Tray |
| Packaging Quantity | 140 |

| General Information | |
|---------------------|--|
| Series | PHE426/F426 |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Notes | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

| Specifications | |
|-----------------------|-------------------------|
| Capacitance | 1.5 uF |
| Capacitance Tolerance | 5% |
| Voltage AC | 220 VAC |
| Voltage DC | 400 VDC, 296 VDC (105C) |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.1% 1kHz |
| Insulation Resistance | 20 GOhms |
| Max dV/dt | 60 V/us |
| Inductance | 6 nH |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)