

**KEMET Part Number: PHE840MA5220KA01R30**  
(F840AH223K275ALW0L)

PHE840M/F840, Film, Metallized Polypropylene, Safety, 0.022 uF, 10%, 275 VAC (X2), 760 VDC, 105°C, Lead Spacing = 10mm



**Dimensions**

<b>L</b>	13mm MAX
<b>H</b>	10.5mm MAX
<b>T</b>	4.5mm MAX
<b>S</b>	10mm +/-0.4mm
<b>LL</b>	30mm NOM
<b>F</b>	0.6mm NOM

**Packaging Specifications**

<b>Packaging:</b>	Bulk, Bag
-------------------	-----------

**General Information**

<b>Series:</b>	PHE840M/F840
<b>Dielectric:</b>	Metallized Polypropylene
<b>Style:</b>	Radial
<b>Features:</b>	EMI Safety
<b>RoHS:</b>	Yes
<b>Lead:</b>	Wire Leads
<b>Safety Class:</b>	X2
<b>Qualifications:</b>	ENEC, UL, cUL
<b>AEC-Q200:</b>	No
<b>THB Performance:</b>	No
<b>Notes:</b>	Not For New Design, Please Check Possible Alternative Parts (AltPart).

**Specifications**

<b>Capacitance:</b>	0.022 uF
<b>Capacitance Tolerance:</b>	10%
<b>Voltage AC:</b>	275 VAC (X2)
<b>Voltage DC:</b>	760 VDC
<b>Temperature Range:</b>	-55/+105°C
<b>Rated Temperature:</b>	105°C
<b>Insulation Resistance:</b>	30 GOhms
<b>Max dV/dt:</b>	100 V/us

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)