


KEMET, L-DMI, Power, 1 uH, 20%



General Information		
Series:	L-DMI	
Style:	SMD Chip	
Description:	Shielded, Surface Mount Inductor	
Features:	High Current Type For Power Supply Line	
RoHS:	Yes	
Winding Type:	Multilayer	

Specifications

Inductance:

Shielded:

Current:

DC Resistance:

Inductance Tolerance:

Temperature Range:

1 uH (1 MHz)

-40/+85°C

1300 mAmps (MAX)

0.12 Ohms (Max)

20%

Yes

Dimensions	
Chip Size	0806
L	2mm +/-0.2mm
W	1.6mm +/-0.2mm
Т	1mm MAX

Packaging Specifications		
Packaging:	T&R	
Packaging Quantity:	3000	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)