



PCB LAYOUT

型号: KH-A1001WF-05A

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 50V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Wafer Nylon 6T, UL94V-0
PIN Phosphoric bronze Tin-plated
Solder tad Phosphoric bronze Tin-plated

| 编号 | 尺寸 (mm) | | |
|-------------|---------|-------|-------|
| | A | B | C |
| A1001WF-02A | 1.00 | 4.00 | 3.20 |
| A1001WF-03A | 2.00 | 5.00 | 4.20 |
| A1001WF-04A | 3.00 | 6.00 | 5.20 |
| A1001WF-05A | 4.00 | 7.00 | 6.20 |
| A1001WF-06A | 5.00 | 8.00 | 7.20 |
| A1001WF-07A | 6.00 | 9.00 | 8.20 |
| A1001WF-08A | 7.00 | 10.00 | 9.20 |
| A1001WF-09A | 8.00 | 11.00 | 10.20 |
| A1001WF-10A | 9.00 | 12.00 | 11.20 |
| A1001WF-11A | 10.00 | 13.00 | 12.20 |
| A1001WF-12A | 11.00 | 14.00 | 13.20 |
| A1001WF-20A | 19.00 | 22.00 | 21.20 |

| 制图 DRAWN | 变更内容 DESCRIPTION | 日期 DATE | GENERAL TOLERANCE | | 制图 Mapping | 钱岳生 2013.07.01 | 料号 PART NO. | KHA1001WF-NA | 版本 REV. | A |
|-------------|---------------------|------------|-------------------|------------|----------------|-------------------|-------------------|-------------------------|--------------|-----|
| | | | X.±0.25 | X.*±2' | 审核 Audit | 张名 2013.07.03 | 品名 TITLE | 1.0贴片 WAFER SMT TYPE | 页次 SHEET | 1/1 |
| | | | .X±0.20 | .X*±1' | 核准 Approved | 张名 2013.07.05 | 客户料号 CUTM. NO. | | | |
| | | | .XX±0.15 | .XX*±0.5' | 单位 Units | MM | 比例 SCALE | 1:1 | 深圳市金航标电子有限公司 | |
| | | | .XXX±0.10 | .XXX*±0.5' | | | WWW.BDS666.COM | 0755-83044319 | | |

单击下面可查看定价，库存，交付和生命周期等信息

[>>kinghelm\(金航标\)](#)