



规格说明: Specifications:
电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触电阻: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf (MAX)
Unmate force: 1.02kgf (MIN)
2. 端子保持力: Terminal Retention
1.2kgf (MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Thermoplastics,
U1 94V-0 PBT White/Black
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
2. 外壳: Shell:
Nickel Plating

深圳市金航标电子有限公司 MMW.BDS666.COM		图号 (DWG NO)		单位 (UNIT): MM
KH-AF900C-10-H6.8 0755-83044319		版本 (REV)	A/0	比例 (SCALE): 1:1
品名 (ITEM NO)	A/F 壳体 10.0 DIP (两脚无卷边 6-8)	日期 (DATE)	2012.06.08	公差 TOLERANCE UNLESS OTHERWISE 1.X ±0.30 2.X ±0.20 3.X ±0.10 4.X ±0.15 5.X ±0.25
料号 (PART NO)		设计 (DESIGN)		
模号 (MODEL NO)	A008-II-2	审核 (CHECKED)		
		核准 (APPROVED)		

单击下面可查看定价，库存，交付和生命周期等信息

[>>kinghelm\(金航标\)](#)