



SPECIFICATIONS

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

| 编 号       | 尺寸 (mm) |       |
|-----------|---------|-------|
|           | A       | B     |
| A2001-02A | 2.00    | 6.00  |
| A2001-03A | 4.00    | 8.00  |
| A2001-04A | 6.00    | 10.00 |
| A2001-05A | 8.00    | 12.00 |
| A2001-06A | 10.00   | 14.00 |
| A2001-07A | 12.00   | 16.00 |
| A2001-08A | 14.00   | 18.00 |
| A2001-09A | 16.00   | 20.00 |
| A2001-10A | 18.00   | 22.00 |
| A2001-11A | 20.00   | 24.00 |
| A2001-12A | 22.00   | 26.00 |
| A2001-16A | 30.00   | 34.00 |

|             |                     |             |                   |             |               |                |                |               |                   |            |                |     |
|-------------|---------------------|-------------|-------------------|-------------|---------------|----------------|----------------|---------------|-------------------|------------|----------------|-----|
| 制图<br>DRAWN | 变更内容<br>DESCRIPTION | 日期<br>DATE  | GENERAL TOLERANCE |             | 制图<br>DRAWING | 张松强            | 料号<br>PART NO. | A2001-NA      |                   | 版本<br>REV. | A              |     |
|             |                     |             | X.±0.25           | X.*2'       |               | 2013、07、01     |                | 品名<br>TITLE   | PH直针              |            | 页次<br>SHEET    | 1/1 |
|             |                     |             | .X±0.20           | .X*±1'      |               | 审核<br>CHECK    |                | 赖积任           | 客户料号<br>CUTM. NO. |            |                |     |
|             |                     |             | .XX±0.15          | .XX*±0.5'   |               | 核准<br>APPROVAL |                | 杜承凯           | 深圳市金航标电子有限公司      |            | WWW.BDS666.COM |     |
| .XXX±0.10   | .XXX*±0.5'          | 单位<br>UNITS | MM                | 比例<br>SCALE | 1:1           | KH-PH-6P-Z     |                | 0755-83044319 |                   |            |                |     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>kinghelm\(金航标\)](#)