



- SPECIFICATION**
1. RATING: 1A DC 30V ;
  2. CONTACT RESISTANCE: Max 30mΩ;
  3. INSULATION RESISTANCE: Min 100MΩ DC 500V;
  4. WITHSTANDING VOLTAGE: AC 500V (50Hz) AT 0.5A FOR 1 MINUTE;
  5. LIFE TEST: ≥5000 CYCLES;
  6. EXTRACTION FORCE: Min 0.3Kg;
  7. INSERTION FORCE: Max 3Kg;
  8. WORK TEMPERATURE: -30° C ~ 70° C;
  9. APPEARANCE IS GOOD FINISHED, NOT EXIST RUST, FLAW CRACK AND BAD PLATING;
  10. SOLDERING CAN MEET 230° C ± 5° C, 3-5 SECOND.

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
⑥	Shunt terminal	1	Brass t=0.4	Silver Plating
⑤	Tip spring	1	Stainless steel t=0.2	Silver Plating
④	Center pin terminal	1	Brass t=0.3	Silver Plating
③	Center pin	1	Brass	CuSn/Nickel Plating
②	Cover	1	PBT UL94V-0	Black
①	Housing	1	PBT UL94V-0	Black

TITLE: DC POWER JACK		DRAWING NO: DC-002F		SHEET: 1 OF 1		GENERAL TOLERANCE	
DATE		3RD ANGLE		SCALE: 1:1		UNIT: mm	
						DIM: X.X±0.3, X.XX±0.2, X.XXX±0.1	
				VER: 2		ANGLE: 3°	

DESIGNER BY:	深圳市金航标电子有限公司	WWW.BDS666.COM
CHECK BY:		
APPROVED BY:	KH-DC-002F-1.3	0755-83044319

REV	DESCRIPTION	DATE
1		
2		

单击下面可查看定价，库存，交付和生命周期等信息

[>>kinghelm\(金航标\)](#)