



规格说明: Specifications:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触电阻: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.0kgf(MIN)

1. 塑胶: Housing:
Hing Temperature Ternmaplastics;

2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC

1. 端子: Contact: Plated Gold in Mating Area
Tin On Solder Tails
端子四周镀50U”(MIN)锡,镀金区域镀100—200U”镀金1U”

铜壳四周镀80U”(MIN)锡

Nickel Plating

| | | | | | | | |
|--------------------------------------|--------|---------|-------|--------------------|------|----------------|-------|
| MANUFACTURE DWG | | 产品图 | | 深圳市金航标电子有限公司 | | WWW.BDS666.COM | |
| TOLERANCE UNLESS OTHERWISE SPECIFIED | | 公差一律按表 | | KH-AF180ZJ-17.5-JB | | 0755-83044319 | |
| .X±0.15 | X.±5° | 日期 | UNIT | 比例 | 比例 | DWG NO. | 版本号 |
| XX±0.05 | .X±2° | 审核 | SCALE | 1:1 | 1:1 | 品名 | 结构特征 |
| XXX±0.02 | .XX±1° | 批准 | 角法 | 第一角法 | 第一角法 | 版本 | 页数 |
| | | APPROVE | VIEW | | | | SHEET |

单击下面可查看定价，库存，交付和生命周期等信息

[>>kinghelm\(金航标\)](#)