


外壳后盖内扣卡点

PCB.LAYOUT

TOL: ± 0.05

备注:  
 电气性能:  
 接触阻抗: 30 毫欧 (最大)  
 绝缘阻抗: 1000 兆欧 (最小)  
 耐高压: 500V AC 一分钟  
 材料:  
 胶芯: PBT/LCP  
 端子: 黄铜C2680  
 外壳: 黄铜C2680/SPCC  
 电镀:  
 端子: 接触区域镀金1u", 焊接区镀亮锡40u"MIN  
 外壳: 全区域镀镍40u"MIN



技术详询

型号: KH-AF90DIP-112

TOLERANCE UNLESS OTHERWISE SPECIFIED
.XXX ±0.10
.XX ±0.20
.X ±0.30
.X* ±3°

产品名称	AF 90度DIP内扣型	
PART NAME:		
料号	See Table	C
PART No:		

REV:	DESCRIPTION	REV BY	APPROVED	DATE	MAIL:	SEE SPECIFICATION	APPROVED
					PROJECTION:	THIRD ANGLE PROJECTION	CHECKED
					UNIT:	SCALE	REV (NO)
						1:1	A
						SHEET	1 OF 1
						DRAWN	LiTao
						DATE	2010.12.21

深圳市金航标电子有限公司

单击下面可查看定价，库存，交付和生命周期等信息

[>>kinghelm\(金航标\)](#)