



RECOMMENDED P.C.B LAYOUT

备注:

1. 产品规格:
 - 1-1. 插入力: 35N MAX.
 - 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER
 - 1-3. 额定电流: 1.0A
 - 1-4. 额定电压: 30V
 - 1-5. 耐久性: 3000 CYCLES MIN.
 - 1-6. 耐电压: 100V AC MIN.
 - 1-7. 接触阻抗: 30mΩ MAX. INITIAL; 40mΩ MAX
 - 1-8. 绝缘电阻: 100MΩ MIN
 - 1-9. 工作温度: -30° TO +80°
2. 材质:
 - 2.1 胶芯: LCP UL94V-0
 - 2.2 端子: C5191, 镍底, 镀金1μ"
 - 2.3 外壳: SUS
3. 所用材质须符合RoHS要求

TOLERANCE UNLESS OTHERWISE SPECIFIED
.XXX ±0.10
.XX ±0.25
.X ±0.35
.X' ±3'

产品名称	MICRO USB B TYPE 180度	
PART NAME:		
料号	91-US10-XXX	C
PART No:		
金航标	WWW.BDS666.COM	
	0755-83044319	

REV:	DESCRIPTION	REV BY	APPROVED	DATE	MATL:	SEE SPECIFICATION	APPROVED
A					PROJECTION:	THIRD ANGLE PROJECTION	CHECKED
					UNIT: MM	SCALE: 1:1	DRAWN: jack
						REV(NO): A	DATE: 2013.02.07
						SHEET: 1 OF 1	

单击下面可查看定价，库存，交付和生命周期等信息

[>>kinghelm\(金航标\)](#)