



- 备注:
- 1: 图中所标注尺寸为 I Q C 必测尺寸.
 - 2: 各零部件组装要牢固可靠.
 - 3: 成品信号参数要达到指定数值.
 - 4: 产品需定数按要求包装好, 运输过程中不能有明显挤压变形等现象.
 - 5: 未经过AFC公司确认, 材质及工艺要求等不能随意更改.

性能参数 Performance parameters

Product Type	4G ANTENNA
Model Type	YL46-4G-SMA-174-3M
Frequency Range	698-960/1710-2700MHz
Band Width	262/990MHz
Vswr	≤2.0
Gain	2.15DB
Impedance	50 OHM
Polarization	Vertical
Radiation	OMNIDIRECTIONAL
Max power	40W
Dimensions	46mm*16mm
Cable	RG174-3000mm
Temperature	-45 -- 85°
connector	SMA-J
Plastic shell	TPEE&ABS

深圳市金航标电子有限公司

DWN BY/DATE ZHOU 2019-5-23	DESG BY/DATE	TOLERANCE .X± .XX±	SCALE	ENG PROJECT NO. YG201905231725	Model Type YL46-4G-SMA-174-3M
----------------------------------	--------------	--------------------------	-------	-----------------------------------	----------------------------------

单击下面可查看定价，库存，交付和生命周期等信息

[>>kinghelm\(金航标\)](#)