





PRODUCT NO. DSDP06LHGET	RoHS compliant
-----------------------------------	-----------------------



- Note:**
- All dimensions are in millimeters.
 - General tolerance: $\pm 0.2\text{mm}$.
 - Material:

- Base: UL94V-0 PBT Thermoplastic (Black).
- Cover: UL94V-0 PBT Thermoplastic (Black/Red/Blue).
- Actuators: UL94V-0 PBT Thermoplastic (White).
- Contact plating: Gold plating over nickel.
- Pitting material: Epoxy.

- Electrical
- Electrical: 2000 Operations per switch 24/VDC, 25mA.
- Non-Switching Rating: 100mA, 50/VDC.
- Switching Rating: 25mA, 24/VDC
- Contact Resistance: 100 mΩ Max. at initial.

- Mechanical
- Mechanical life: 2000 Operations per switch.
- Stroke: 30°
- Operation Temp: -20°C to 70°C.
- Storage Temp: -40°C to 85°C.

6. PART NUMBER DESCRIPTION:

DS DP XX L H G E I

- [Packing: T-Tube R-Seal]
- [Finish: 1 μ " 3 μ " Gold-plated R=10 μ " Gold-plated]
- [Finish: 6-Full Gold S-Contact-Gold-plated, Terminal-Tin-Plated]
- [Terminal: S-SMD type H-Straight.....]
- [Actuator: T-Tape sealed S-F/w profile W/O Tape L-Extension]
- [HP=Half-Pitch IC=IC type PV=Plano type WB=WB type]

TOLERANCE UNLESS OTHERWISE SPECIFIED		INSTRUCTION	
LINE	ANGLE	CHIT	PROJECTION
0 ± 0.40	0 ± 1°		
.00 ± 0.30	.0 ± 0.5°		
.000 ± 0.20	.00 ±		
DESIGN	UI ER TIN	3013/07/08	
DRAWING			
CHECK			
APPVAL			
TITLE		BY DSDP SERIES PITCH 2.54mm	
PRODUCT FAMILY		DSDP SERIES	
PART NO.		DSDP06LHGET	
DRAWING		DRAWING-1	
FILE NO.	UNIT	SCALE	SHEET
A4	mm	1:1	1 OF 1

东莞市广誉实业有限公司
Dongguan Kingtek Industrial Co., Ltd.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KINGTEK\(广督\)](#)