




PRODUCT NO.	DSDA121HERFT
RoHS compliant	




- Note:**
- All dimensions are in millimeters.
  - General tolerance:  $\pm 0.2\text{mm}$ .
  - Material:

- Base: UL94V-0 PBT Thermoplastic (Black).
- Cover: UL94V-0 PBT Thermoplastic (Black/Red/Blue).
- Actuators: UL94V-0 PA66 Thermoplastic (White).
- Contact plating: Gold plating over nickel.
- Pitting material: Epoxy.

- Electrical
  - Electrical: 2000 Operations per switch 24/VDC, 25mA.
  - Non-Switching Rating: 100mA, 50/VDC.
  - Switching Rating: 25mA, 24/VDC
  - Contact Resistance: 100 mΩ Max. at initial.
- Mechanical
  - Mechanical life: 2000 Operations per switch.
  - Stroke: 2.0mm.
  - Operation Temp: -20°C to 70°C.
  - Storage Temp: -40°C to 85°C.

**6. PART NUMBER DESCRIPTION:**



TOLERANCE UNLESS OTHERWISE SPECIFIED		INSTRUCTION	
LINE	ANGLES	CHPT	PROJECTION
0 ± 0.40	0 ± 1°		
.00 ± 0.30	.0 ± 0.5°		
.000 ± 0.20	.00 ±		
DESIGN	UI ER TIN	3013/01/02	
DRAWING			
CHECK			
APPROV			
TITLE		BY DSDA SERIES PITCH 2.54mm	
PRODUCT FAMILY		DSDA SERIES	
PART NO.		DSDA121HERFT	
FILE NO.		DSDA121HERFT-1	
SIZE	UNIT	SCALE	REV.
A4	MM	1:1	A

单击下面可查看定价，库存，交付和生命周期等信息

[>>KINGTEK\(广督\)](#)