



# Photocoupler

## Product Data Sheet

### LTV-305X

Spec No.: DS70-2014-0079

Effective Date: 07/15/2016

Revision: B

**LITE-ON DCC**

**RELEASE**

BNS-OD-FC001/A4

## Photocoupler LTV-305X series

### 1. DESCRIPTION

#### 1.1 Features

- Isolation voltage between input and output  $V_{iso}$  : 3,750Vrms
- 4pin MFP non zero-cross optoisolators triac driver output
- High repetitive peak off-state voltage  $V_{DRM}$  : Min. 600V
- High critical rate of rise of off-state voltage (  $dV/dt$  : MIN. 1000V /  $\mu s$  )
- Mini-flat package :  
2.0mm profile : LTV-3050, LTV-3051, LTV-3052, LTV-3053
- Safety approval  
UL 1577  
cUL CA5A  
VDE DIN EN60747-5-5 (VDE 0884-5)
- RoHS Compliance  
All materials be used in device are followed EU RoHS directive (No.2002/95/EC).
- ESD pass HBM 8000V / MM2000V
- MSL class1


#### 1.2 Applications

- Motor Controls
- Solid state relays
- For triggering high power thyristor and triac
- Household use equipment

## Photocoupler LTV-305X series

### 2. PACKAGE DIMENSIONS

#### 2.1 LTV-305X series



#### Notes :


1. 1-digit Year date code, 2-digit work week.
2. Factory identification mark shall be marked (X: China -TJ)
3. I<sub>FT</sub> Rank
4. "4" or "V" for VDE option.

\*All dimensions in millimeters.


## Photocoupler LTV-305X series

### 3. TAPING DIMENSIONS

#### 3.1 LTV-305X-TP



#### 3.2 LTV-305X



Description	Symbol	Dimension in mm (inch)
Tape wide	W	12±0.3 (0.472)
Pitch of sprocket holes	$P_0$	4±0.1 (0.157)
Distance of compartment	F	5.5±0.1 (0.217)
	$P_2$	2±0.1 (0.079)
Distance of compartment to compartment	$P_1$	8±0.1 (0.315)

#### 3.3 Quantities Per Reel

Package Type	LTV-305X series
Quantities (pcs)	3000

## Photocoupler LTV-305X series

### 4. RATING AND CHARACTERISTICS

#### 4.1 Absolute Maximum Ratings at Ta=25°C

	Parameter	Symbol	Rating	Unit
Input	Forward Current	$I_F$	50	mA
	Reverse Voltage	$V_R$	6	V
	Power Dissipation	$P_D$	70	mW
	Junction Temperature	$T_J$	125	°C
Output	Off-State Output Terminal Voltage	$V_{DRM}$	600	V
	Peak Repetitive Surge Current ( PW=1ms, 120pps )	$V_{TSM}$	1	A
	Collector Power Dissipation	$P_C$	300	mW
	Junction Temperature	$T_J$	125	°C
	Total Power Dissipation	$P_{tot}$	330	mW
*1.	Isolation Voltage	$V_{iso}$	3750	$V_{rms}$
	Ambient Operating Temperature Range	$T_A$	-55 ~ +115	°C
	Storage Temperature	$T_{stg}$	-55 ~ +150	°C
*2.	Soldering Temperature	$T_L$	260	°C

\*1. AC For 1 Minute, R.H. = 40 ~ 60%

Isolation voltage shall be measured using the following method.

- (1) Short between anode and cathode on the primary side and between collector and emitter on the secondary side.
- (2) The isolation voltage tester with zero-cross circuit shall be used.
- (3) The waveform of applied voltage shall be a sine wave.

\*2. For 10 Seconds

## Photocoupler LTV-305X series

### 4.2 ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C

Parameter		Symbol	Min.	Typ.	Max.	Unit	Test Condition
Input	Forward Voltage	$V_F$	—	1.15	1.5	V	$I_F=20\text{mA}$
	Reverse Current	$I_R$	—	—	10	$\mu\text{A}$	$V_R=6\text{V}$
Output	*1 Peak Blocking Current, Either Direction	$I_{\text{DRM}}$	—	10	100	nA	$V_{\text{DRM}}=600\text{V}$
	Peak On-State Voltage, Either Direction	$V_{\text{TM}}$	—	1.7	3	V	$I_{\text{TM}}=100\text{ mA Peak}$
	*2 Critical Rate of Rise of Off-State Voltage	$dv/dt$	1000	—	—	V/ $\mu\text{s}$	
COUPLED	*3 Led Trigger Current, Current Required to Latch Output, Either Direction	LTV-3050	—	—	30	mA	Main Terminal Voltage = 3V
		LTV-3051	—	—	15		
		LTV-3052	—	—	10		
		LTV-3053	—	—	5		
	Holding Current, Either Direction	$I_H$	—	250	—	$\mu\text{A}$	

\*1 Test voltage must be applied within  $dv/dt$  rating.

\*2 This is static  $dv/dt$ . Commutating  $dv/dt$  is a function of the load-driving thyristor(s) only.

\*3 All devices are guaranteed to trigger at an  $I_F$  value less than or equal to max  $I_{FT}$ .

# Photocoupler LTV-305X series

## 5. CHARACTERISTICS CURVES (TYPICAL PERFORMANCE)

Fig.1 Forward Current vs. Ambient Temperature




Fig.2 On-state Current vs. Ambient Temperature




Fig.3 Minimum Trigger Current vs. Ambient Temperature




Fig.4 Forward Current vs. Forward Voltage




Fig.5 On-state Voltage vs. Ambient Temperature





Fig.6 Holding Current vs. Ambient Temperature



# Photocoupler LTV-305X series

Fig.7 Repetitive Peak Off-state Current vs. Temperature






Fig.8 On-state Current vs. On-state Voltage



Basic Operation Circuit

Medium/High Power Triac Drive Circuit






# Photocoupler LTV-305X series

## 6. TEMPERATURE PROFILE OF SOLDERING

### 6.1 IR Reflow soldering (JEDEC-STD-020C compliant)

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.

Profile item	Conditions
Preheat	
- Temperature Min ( $T_{Smin}$ )	150°C
- Temperature Max ( $T_{Smax}$ )	200°C
- Time (min to max) (ts)	90±30 sec
Soldering zone	
- Temperature ( $T_L$ )	217°C
- Time ( $t_L$ )	60 sec
Peak Temperature ( $T_P$ )	260°C
Ramp-up rate	3°C / sec max.
Ramp-down rate	3~6°C / sec



# Photocoupler LTV-305X series

## 6.2 Wave soldering (JEDEC22A111 compliant)


One time soldering is recommended within the condition of temperature.

Temperature:  $260+0/-5^{\circ}\text{C}$

Time: 10 sec.

Preheat temperature: 25 to  $140^{\circ}\text{C}$

Preheat time: 30 to 80 sec.



## 6.3 Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.


Temperature:  $380+0/-5^{\circ}\text{C}$

Time: 3 sec max.

**Photocoupler  
LTV-305X series**

**7. RRECOMMENDED FOOT PRINT PATTERNS (MOUNT PAD)**

Unit: mm



**Photocoupler  
LTV-305X series**

**8. NAMING RULE**

**LTV-305(X)(1)**

DEVICE PART NUMBER

Please refer to Electrical Optical Characteristics Table on Page P5

(1) TAPING TYPE (TP or no suffix)

Example : LTV-3051-TP1

**LTV305(X)(1)-V**

DEVICE PART NUMBER

Please refer to Electrical Optical Characteristics Table on Page P5

(1) TAPING TYPE (TP or no suffix)

(2) VDE option

Example : LTV3051TP1-V

**9. NOTES**

- LiteOn is continually improving the quality, reliability, function or design and LiteOn reserves the right to make changes without further notices.
- The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.
- For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.
- When requiring a device for any "specific" application, please contact our sales in advice.
- If there are any questions about the contents of this publication, please contact us at your convenience.
- The contents described herein are subject to change without prior notice.
- Immerge unit's body in solder paste is not recommended.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Lite-On\(光宝\)](#)