

MATERIAL	PLATING	NOM. PLATING WT. (GRS)	VENDOR
BeCu	Ag/Cu	Ag=.017; Cu=.0087	FORMCO

PLATE FUSE CLIP 124016-2 AS FOLLOWS:

COMM BRIGHT SILVER .0001" MIN
OVER .00005" MIN COPPER FLASH

-	PS001034	CYANIDE COPPER	0.024	LB
-	095400	SILVER PLATE	1.600	TOZ
-	124016-2	FUSE CLIP	1000	EA
NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M

BILL OF MATERIAL

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

\bigcirc	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
\bigcirc ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

																		G	F	LTR	
																			85458D-ADDED CHART 4/19/07	82565D-REVISE & REDRAW 10/15/02	REVISION
																					CHK

COPIES TO	MATL SPEC	FINISH
1 9 18	DRW TRG	DATE 10/15/02
2 10 19	CHK	DATE
3 12 20	APPD	DATE
4 13 21		RAW STK WT
5 14 23	LBS/M	
6 15 33	TOLERANCE UNLESS OTHERWISE SPECIFIED	
7 16 43	TWO PLACE DEC \pm .01	FRACTION \pm
8 17 53	THREE PLACE DEC \pm .005	ANGULAR \pm 1°
TITLE		
FUSE CLIP		
REVISION	DRWG. NO.	FINAL
G	01230002Z	



CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)