


SPECIALTY PRODUCTS

ATO® Diode



MINI® Diode



Specifications

Operating Temp.: -40°C to +85°C
 Power Rating: 1/4 W Max
 Body Material: Thermoplastic
 Term. Material: C.R.S. (Ni/Zn Plated)
 Term. Retention: 25 N

| Part Number | Type | Current Rating | Peak Inverse Voltage | Housing Color | Part Quantity |
|-------------|------|----------------|----------------------|---------------|---------------------|
| 02400103_ | ATO | 1 A | 400 Volts | Black | Z = 1500 / LXN = 50 |
| 02400104P | MINI | 1 A | 400 Volts | Black | 2000 |
| 02400110P | MINI | 1 A | 400 Volts | Black | 2000 |
| 02400113P | MINI | 1 A | 400 Volts | Black | 2000 |
| 02400115P | MINI | 1 A | 1000 Volts | Green | 2000 |
| 02400119P | MINI | 1 A | 400 Volts | Black | 2000 |
| 02400120P | MINI | 1.5 A | 400 Volts | Brown | 2000 |

* 1 A Diode in ATO® size housing. The cathode connector is rotated 90°

ATO® Resistor



MINI® Resistor



Specifications

Body Material: Thermoplastic
 Term. Material: C.R.S. (Ni/Zn Plated)
 Term. Retention: 25 N

Operating Temp for ATO is -20°C to +85°C
 Power Rating: 1/4 W Max

Operating Temp.: -40°C to +85°C
 MINI Resistor Power Rating is up to 1/2 W

| Part Number | Type | Current Rating | Wattage | Housing Color | Part Quantity |
|-------------|------|----------------|---------|---------------|---------------|
| 02400105Z | ATO | 10K ohm | ¼ Watt | White | 1500 |
| 02400116P | ATO | 750 ohm | ¼ Watt | Yellow | 2000 |
| 02400106P | MINI | 620 ohm | ½ Watt | Grey | 2000 |
| 02400107P | MINI | 121 ohm | ½ Watt | Grey | 2000 |
| 02400108P | MINI | 5.1K ohm | ¼ Watt | Blue | 2000 |
| 02400111P | MINI | 16.9 ohm | ¼ Watt | Red | 2000 |
| 02400112P | MINI | 121 ohm | ½ Watt | Green | 2000 |
| 02400114P | MINI | 240 ohm | ½ Watt | Green | 2000 |
| 02400118P | MINI | 500 ohm | ½ Watt | Grey | 2000 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)