

# POWR-GARD® Blocks & Holders

## LFPSC DEAD-FRONT FUSE HOLDERS

600 V • 10 x 38 mm • Class CC



### Description

Littelfuse LFPSC Class CC 10 x 38 mm dead-front holders feature optional LED indication, DIN rail mounts and a small space saving design. These high SCCR rated holders provide optimum touch-safe protection to personnel and have a large clamping range with dual wire rated terminals.

### Features

- Indicating and non-indicating options available
- IP20 degree of protection
- Dual LED indication distinguishes polarity in DC applications
- Small compact design offers ultimate flexibility
- 35 mm DIN-Rail Mountable
- 1-, 2-, 3- and 4-pole configurations
- Easy installation and fuse removal with no additional pullers or tools required

### Web Resources

Download technical documents at:  
[littelfuse.com/lfpsc](http://littelfuse.com/lfpsc)

### Recommended Fuses

CCMR, KLDR, KLKR

### Terminal Information

TERMINAL TYPE	WIRE TYPE	NUMBER OF WIRES	WIRE SIZE	TORQUE
Pressure Plate	75 <sup>+</sup> Max CU Only Stranded	1	18-8 AWG (.75-25 mm <sup>2</sup> )	18-22 lb-in (2-2.5 N-m)
		1	6-4 AWG	22-26 lb-in
		2 <sup>1</sup>	18-6 AWG (.75-10 mm <sup>2</sup> )	18-22 lb-in (2-2.5 N-m)

<sup>1</sup>Must be the same cross-sectioned size

### Ordering Information


VOLTAGE	AMPERE	SCCR Rating	POLES	FUSE TYPE	SERIES	NON-INDICATING		INDICATING		PACK QUANTITY
						CATALOG NUM.	ORDERING NUM.	CATALOG NUM.	ORDERING NUM.	
600 V ac/dc	30 A	200 kA	1	Class CC	LFPSC	LFPSC001	LFPSC0001Z	LFPSC001ID	LFPSC0001ZXID	12
			2		LFPSC	LFPSC002	LFPSC0002Z	LFPSC002ID	LFPSC0002ZXID	6
			3		LFPSC	LFPSC003	LFPSC0003Z	LFPSC003ID	LFPSC0003ZXID	4
			4		LFPSC	LFPSC004	LFPSC0004Z	LFPSC004ID	LFPSC0004ZXID	3

**Disclaimer Notice** – Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/product-disclaimer](http://www.littelfuse.com/product-disclaimer).

### Specifications


<b>Voltage Rating</b>	600 V ac/dc
<b>Ampere Rating</b>	30 A
<b>SCCR Rating</b>	200 kA
<b>Power Acceptance</b>	3W Maximum
<b>Indication Voltage Range</b>	110 – 600 V ac/dc
<b>Terminal Type</b>	Pressure Plate
<b>Material</b>	Thermoplastic
<b>Flammability Rating</b>	UL94 V-0, self-extinguishing
<b>Approvals</b>	UL Listed (File: E14721) CSA Certified
<b>Environmental</b>	RoHS compliant, Lead (Pb) free

### Dimensions mm (inches)



### Multi-Pole Assembly Kits

POLES	PINCER QTY.	PIN QTY.	ASSEMBLY SETS	ORDERING NUMBER
2	30	10	10 pack	LFPHV2PAK
3	60	20	10 pack	LFPHV3PAK



单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)