



RTD ELEMENT RESISTANCE @ 0°C (+32°F) = 1,000 Ω ± 0.06%  
 RTD ELEMENT ACCURACY @ 0°C (+32°F) = ± 0.15%  
 TCR = 3,850ppm/°C  
 RTD ELEMENT DIN 43760 ACCURACY CLASS = "A"  
 MAXIMUM TEMPERATURE RATING = +287.8°C (+550°F)

CABLE: 26 AWG, STRANDED CONDUCTOR, TWO CONDUCTOR,  
 GRASS BRAID INSULATED, GLASS BRAID JACKETED,  
 0.045" X 0.075" NOMINAL O.D.

SEE MANUFACTURING SPECIFICATION (LAYER 1)

REV	REVISION RECORD	DATE	APP
"A"	CABLE WAS 10" ± 1" LONG & FIXED WIRE GAUGE (TYPO)	07/07/16	DD
NONE	RELEASE TO PRODUCTION	07/06/16	DD

SCALE	NONE	U.S. SENSOR CORP. © COPYRIGHT
DRAWN BY	DAN DANKERT	
DATE	07/06/16	714-639-1000 www.ussensor.com
REV.	"A"	RTD PROBE ASSY
LAYER	0 OF 2	P/N USW4260

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)