



- NOTES:
1. NUT IS TO ACCEPT A TORQUE OF 18 LB.-IN. WITHOUT CRACKING OR STRIPPING
 2. THE STARTING POINT OF THE LEAD THREAD CANNOT EXCEED .030 FROM SURFACE [A].
 3. "FLASH EXTENDING ABOVE SURFACE [A] CANNOT EXCEED .006 HIGH AND .004 THICK.

PACKAGING NOTES:
 PLACE IN TOTE -580599 LINED WITH POLY BAG -890-750
 LABEL TOTE WITH -914-796 PRINTED PER GENERAL LABEL SPEC. LS-000003.

LB	2.25
QTY/M	U/M
NO	057295
NO COMPONENT NO	DESCRIPTION

BILL OF MATERIAL	
CDPIES TO	MATL SPEC
1	9 18 DRW KAM
2	10 19 DATE 1/23/97 SCALE 4:1
3	12 20 CHK SUPER DRW
4	13 21 APPD RAW STK WT
5	14 23
6	15 33
7	16 43
8	17 53

TOLERANCE UNLESS OTHERWISE SPECIFIED
 TWO PLACE DEC ±.01 FRACTION ±
 THREE PLACE DEC ±.005 ANGULAR ±1°

FINISH

HEX NUT, MOLDED

LTR	REVISION	CHK	APD
K	39068C-REVISE & REDRAWN IN NEW STRUCTURE 4/16/98 KAM		
L	39682C-CHG. 0.845 TO .7896 03/22/99 PJM		
M	80635C-CHG. .7896 TO 2.25 08/22/00 PJM		

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS -MINIMUM CP VALUE
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF TIGHT TOLERANCE TO BE USED FOR MEASUREMENT AND INSPECTION. INSPECTOR MUST SELF-INSPECT ON INSTRUCTIONS.
 DIMENSIONS OF DIMENSIONS -MINIMUM CP VALUE
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF TIGHT TOLERANCE TO BE USED FOR MEASUREMENT AND INSPECTION. INSPECTOR MUST SELF-INSPECT ON INSTRUCTIONS.
 DIMENSIONS OF DIMENSIONS -MINIMUM CP VALUE
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF TIGHT TOLERANCE TO BE USED FOR MEASUREMENT AND INSPECTION. INSPECTOR MUST SELF-INSPECT ON INSTRUCTIONS.

CDPIES TO	MATL SPEC
1	9 18 DRW KAM
2	10 19 DATE 1/23/97 SCALE 4:1
3	12 20 CHK SUPER DRW
4	13 21 APPD RAW STK WT
5	14 23
6	15 33
7	16 43
8	17 53

TOLERANCE UNLESS OTHERWISE SPECIFIED
 TWO PLACE DEC ±.01 FRACTION ±
 THREE PLACE DEC ±.005 ANGULAR ±1°

FINISH

HEX NUT, MOLDED

REVISED BY: M
 DRAWING NO: 903-097
 DESKTOP: ILLINOIS 60016
 Litelife
 DESKTOP: ILLINOIS 60016

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)