



NOTE:

- MATERIAL: MEDIUM DENSITY, CLOSED CELLULAR NEOPRENE SPONGE, APPROX. 50-70 DUROMETER. BLACK COLOR
- SURFACES INDICATED BY THIS DIMENSION TO HAVE NO SKIN (BOTH SIDES) AND MAY HAVE A WAFFLED FINISH OF MIN DEPTH.

SOURCE: SEAL RING'S
OR ENG'R APPROVED EQUAL

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
BILL OF MATERIAL				
UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.				
O	DENOTES CRITICAL CHARACTERISTICS.			
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE 1.33			
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.			
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.			
COPIES TO		MATL SPEC	FINISH	
1	9 18	DRW KAM	DATE 4/8/98	SCALE 4:1
2	10 19	CHK	DATE	SUPER DRW
3	12 20	APPD	DATE	RAW STK WT
4	13 21	TOLERANCE UNLESS OTHERWISE SPECIFIED		
5	14 23	TWO PLACE DEC ±.01		FRACTION
6	15 33	THREE PLACE DEC ±.005		ANGULAR
7	16 43	TITLE		
8	17 53	WASHER RUBBER		

CH	REVISION	DATE	BY	APP'D	DESCRIPTION
	F	3/21/20			REVISED & REORAN ON NEW FORMAT 6/12/98 JMB
	G	7/27/98			CHG. TITLE BJJ

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)