


AK6-Y Series



Agency Recognitions


| AGENCY | AGENCY FILE NUMBER |
|--------|--------------------|
| | E128662 |

Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|--------------------------------------|------------------|------------|------|
| Operating Storage Temperature Range | T _{STG} | -55 to 150 | °C |
| Operating Junction Temperature Range | T _J | -55 to 125 | °C |
| Current Rating ¹ | I _{PP} | 6 | kA |

Note:
1. Rated I_{pp} measured with 8/20µs pulse.

Functional Diagram



Description

The AK6-Y series of high power TVS diode is specially designed for meeting severe surge test environment of both AC and DC line protection applications. It features a very fast response and ultra low clamping characteristics as compared to MOVs (Metal Oxide Varistors). It accomplishes this by virtue of the Littelfuse Foldback™ technology, which provides a clamping voltage lower than the avalanche voltage (but above the rated working voltage); therefore, any voltage rise due to increased current conduction is maintained at a minimum magnitude, providing the best possible protection level. These AK components can be connected in series and / or parallel to create a very high surge current protection solution.

Features

- Recognized to UL 497B as an Isolated Loop Circuit Protector
- Both reflow and wave soldering capable
- Very low clamping voltage
- Ultra compact: less than one-tenth the size of traditional discrete solutions
- Sharp breakdown voltage
- Low slope resistance
- Bi-directional
- Foldback technology for superior clamping factor
- Symmetric in leads width for easier soldering during assembly.
- IEC-61000-4-2 ESD 15kV(Air), 8kV (Contact)
- ESD protection of data lines in accordance with IEC 61000-4-2
- EFT protection of data lines in accordance with IEC 61000-4-4
- Halogen-free and RoHS compliant
- Glass passivated junction
- Pb-free E4 means 2nd level interconnect is Pb-free and the terminal finish material is silver

Electrical Characteristics (T_A=25°C unless otherwise noted)

| Part Numbers | Part Marking | Standoff Voltage (V _{SO}) Volts | Max. Reverse Leakage (I _R) @ V _{SO} µA | Typical I _R @ 85°C (µA) | Reverse Breakdown Voltage (V _{BR}) @ I _T | | Test Current I _T (mA) | Max. Clamping Voltage V _{CL} @ I _{PP} Peak Pulse Current (I _{PP}) (Note 1) | | Max. Temp Coefficient OF V _{BR} (%/°C) | Max. Capacitance 0 Bias 10kHz (nF) | Agency Approval |
|--------------|--------------|---|---|------------------------------------|---|-----------|----------------------------------|--|----------------------|---|------------------------------------|-----------------|
| | | | | | Min Volts | Max Volts | | V _{CL} Volts | I _{PP} Amps | | | |
| AK6-030C-Y | 6-030C | 30 | 10 | 15 | 32 | 37 | 10 | 90 | 6,000 | 0.1 | 11.0 | X |
| AK6-058C-Y | 6-058C | 58 | 10 | 15 | 64 | 70 | 10 | 110 | 6,000 | 0.1 | 8.0 | X |
| AK6-066C-Y | 6-066C | 66 | 10 | 15 | 72 | 80 | 10 | 120 | 6,000 | 0.1 | 6.0 | X |
| AK6-076C-Y | 6-076C | 76 | 10 | 15 | 85 | 95 | 10 | 140 | 6,000 | 0.1 | 6.5 | X |
| AK6-170C-Y | 6-170C | 170 | 10 | 15 | 180 | 220 | 10 | 260 | 6,000 | 0.1 | 2.8 | X |
| AK6-190C-Y | 6-190C | 190 | 10 | 15 | 200 | 245 | 10 | 290 | 6,000 | 0.1 | 2.5 | X |
| AK6-240C-Y | 6-240C | 240 | 10 | 15 | 250 | 285 | 10 | 340 | 6,000 | 0.1 | 2.0 | X |
| AK6-380C-Y | 6-380C | 380 | 10 | 15 | 401 | 443 | 10 | 520 | 6,000 | 0.1 | 1.4 | X |
| AK6-430C-Y | 6-430C | 430 | 10 | 15 | 440 | 490 | 10 | 625 | 6,000 | 0.1 | 1.0 | X |

Note: Using 8/20µs wave shape as defined in IEC 61000-4-5.

Figure 1 - Peak Power Derating




Figure 2 - Pulse Waveform




Figure 3 - Typical Peak Pulse Power Rating Curve




Figure 4 - Typical V_{BR} Vs Junction Temperature






Figure 5 - Surge Response (8/20 Surge current waveform)



Note: The power dissipation causes a change in avalanche voltage during the surge and the avalanche voltage eventually returns to the original value when the transient has passed.


Soldering Parameters

| | | |
|--|------------------------------------|-------------------------|
| Reflow Condition | | Lead-free assembly |
| Pre Heat | - Temperature Min ($T_{s(min)}$) | 150°C |
| | - Temperature Max ($T_{s(max)}$) | 200°C |
| | - Time (min to max) (t_s) | 60 – 120 secs |
| Average ramp up rate (Liquidus Temp (T_L) to peak) | | 3°C/second max |
| $T_{s(max)}$ to T_A - Ramp-up Rate | | 3°C/second max |
| Reflow | - Temperature (T_L) (Liquidus) | 217°C |
| | - Time (min to max) (T_S) | 60 – 150 seconds |
| Peak Temperature (T_p) | | 260 ^{+0/-5} °C |
| Time within 5°C of actual peak Temperature (t_p) | | 30 seconds |
| Ramp-down Rate | | 6°C/second max |
| Time 25°C to peak Temperature (T_p) | | 8 minutes Max. |
| Do not exceed | | 260°C |



Flow Soldering (Solder Dipping)


| | | |
|---|------------------------------------|-------------------------|
| Reflow Condition | | Lead-free assembly |
| Pre Heat | - Temperature Min ($T_{s(min)}$) | 140°C |
| | - Temperature Max ($T_{s(max)}$) | 160°C |
| | - Time to Pre-Heat Temp | 60 – 150 secs |
| Average ramp up rate to Pre-Heat Temp | | 5°C/second max |
| Peak Temperature (T_p) | | 260 ^{+0/-5} °C |
| Average ramp up rate (pre-heat to T_p) | | 5°C/second max |
| Time within actual peak Temperature Max | | 6 seconds |
| Ramp-down Rate | | 5°C/second max |



Physical Specifications


| | |
|-----------------|---|
| Weight | Contact manufacturer |
| Case | UL Recognized compound meeting flammability rating V-0 |
| Terminal | Silver plated leads, solderable per MIL-STD-750 Method 2026 |

Dimensions




| Dimensions | Inches | Millimeters |
|-----------------------------|---|----------------|
| A | 0.950 +/- 0.040 | 24.15 +/- 1.00 |
| B | 0.095 +/- 0.024 | 2.4 +/- 0.60 |
| C | 0.236 +/- 0.040 | 6.00 +/- 1.00 |
| D | 0.570 max. | 14.48 max. |
| E | 0.050 +/- 0.002 | 1.270 +/- 0.05 |
| F | 0.500 max. | 12.70 max. |
| G - 030C-Y | 0.161 +/- 0.040 | 4.10 +/- 1.00 |
| G - 058C-Y/066C-Y 076C-Y | 0.189 +/- 0.040 | 4.8 +/- 1.00 |
| G - 170C-Y/190C-Y | 0.320 +/- 0.040 | 8.13 +/- 1.00 |
| G - 240C-Y | 0.370 +/- 0.040 | 9.4 +/- 1.00 |
| G - 380C-Y/430C-Y | 0.543 +/- 0.040 | 13.8 +/- 1.00 |
| L1/L2 | L1= L2 tolerance +/- 0.04 inch (1.0 mm) | |

Part Marking System




Apply to P/N listed below:
AK6-030C-Y
AK6-058C-Y
AK6-066C-Y
AK6-076C-Y



Apply to P/N listed below:
AK6-170C-Y
AK6-190C-Y
AK6-240C-Y
AK6-380C-Y
AK6-430C-Y

Part Numbering System



Packing Options

| Part Number | Component Package | Quantity | Packaging Option |
|--------------|-------------------|-----------|------------------|
| AK6-XXXX-Y | AK Package | 56pcs/Box | Bulk |
| AK6-XXXX-Y12 | AK Package | 12pcs/Box | Bulk |

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)