

USP9728 Thermistor Probe




Description

Littelfuse offers Stainless probe assemblies suitable for a wide range of temperature sensing applications. If the dimensions and electrical characteristics on this product won't work for your requirements, please contact us for further assistance.

Features

- Tight Tolerance
- Flange with Two #6 Mounting Holes
- Glass Braid Insulated, Glass Braid Jacketed Cable
- Molex Connectors
- High Temperature Capability to 300°C

Dimensions




Dimensions in inches.

A	B	C	D	E
1.750" ±1.250"	96.0" ±4.50"	2.250" ±0.250"	0.250" ±0.005"	0.032" ±0.008"

F	G	H	I
0.314" ±0.010" Dia	0.815" ±0.015"	0.145" ±0.010"	0.595" Nom C-C

Part Numbering System



Note: Not all combinations of Part Number codes are available. Contact Littelfuse for details.

Specifications

Part Number	Resistance Ohms @25°C	Resistance Tol. ± % @ 25°C	R-T Curve	Temperature Coefficient (% / °C) @ 25°C	Beta (K) 0-50°C	Temperature Range (°C)
USP9728	100000	2	J	-4.4	3892	-55 to +300

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littelfuse.com/disclaimer-electronics

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)