

USP5510 Thermistor Probe




Description

Littelfuse offers Flag Terminal probe housings suitable for a wide range of temperature sensing applications. If the dimensions on this product won't work for your requirements, please contact us for further assistance.

Features

- High Accuracy
- #6 Mounting Hole
- Teflon Insulated Lead Wire
- 150°C Max Operating Temperature


Dimensions



Dimensions in inches.

A	B	C
0.250" ± 0.070" Strip	12.0" ± 0.750"	0.645" ± 0.025"
D	E	F
0.310" ± 0.015"	0.145" Nom Stud	0.220" Nom Diam

Part Numbering System



Note: Not all combinations of Part Number codes are available. Contact Littelfuse for details.

Specifications

Part Number	Resistance Ohms @25°C	Accuracy (°C) 0 - 70°C	R-T Curve	Temperature Coefficient (% / °C) @ 25°C	Beta (K) 0-50°C	Temperature Rating (°C)
USP5510	10000	0.5	J	-4.4	3892	-55 to +150

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littelfuse.com/disclaimer-electronics

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)