


DESIGN DATA

1. O.D. = .220 REF.
2. TOTAL COILS = 14
3. ACTIVE COILS = 12 ±2 COILS
4. RATE = 7.5 LBS./IN.
5. SOLID HEIGHT = .395 MAX.
6. FORCE @ .815 LENGTH = 2.7 LBS ±0.3 LBS.
7. ENDS SQUARED
8. SPRING MAY BE LEFT OR RIGHT HAND WOUND.

NOTES:

1. PACKAGE 8000 SPRINGS IN TOTE -580566 AND COVER.



UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

CPK DENOTES CRITICAL CHARACTERISTICS.

CPK DENOTES CPK DIMENSIONS - MINIMUM CPK VALUE 1.0

CPK DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF THE VARIATION OF THE MEASUREMENT PROCEDURE FOR MEASUREMENT OF THIS CHARACTERISTIC TO THE TOLERANCE SPECIFIED IN THE INSTRUCTIONS.

CPK DENOTES CP DIMENSIONS - MINIMUM CP VALUE 1.0. CPK DENOTES CP DIMENSIONS WITHIN THE DIMENSIONAL LIMITATIONS SPECIFIED IN THE INSTRUCTIONS. CPK DENOTES CP DIMENSIONS FOR MAXIMUM TOOL LIFE.

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
1	-069101	φ-.026 GALV. WIRE	1,300	LB

BILL OF MATERIAL

MATERIAL SPEC		FINISH	
CDPIES TO	DRW	DATE	SCALE
1	9 18	1/13/99	4=1
2	10 19		SUPER DRW
3	12 20		RAW STK WT
4	13 21		
5	14 23		
6	15 33		
7	16 43		
8	17 53		

TOLERANCE UNLESS OTHERWISE SPECIFIED
 TWO PLACE DEC ±.01
 THREE PLACE DEC ±.005
 ANGULAR ±1°

LTR	REVISION	CHK	APD
G	39059C- REVISE & REDRAWN ON NEW FORMAT 3/31/98 JMB		
H	39580B-MODIFY PACKAGING NOTE 01/13/99 PJM		

TITLE

SPRING

DESIGNER: JMB
 DRAWN: H
 ILLINOIS 60016

Litefuse®

DESIGNER: JMB
 DRAWN: H
 ILLINOIS 60016

-912-200

单击下面可查看定价，库存，交付和生命周期等信息

[>>Littelfuse\(美国力特\)](#)