


LMBT2907ALT1G

S-LMBT2907ALT1G

General Purpose Transistors PNP Silicon


1. FEATURES

- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.



2. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LMBT2907ALT1G	2F	3000/Tape&Reel
LMBT2907ALT3G	2F	10000/Tape&Reel



3. MAXIMUM RATINGS(Ta = 25°C)

Parameter	Symbol	Limits	Unit
Collector–Emitter Voltage	V _{CEO}	-60	V
Collector–Base Voltage	V _{CBO}	-60	V
Emitter–Base Voltage	V _{EBO}	-5	V
Collector Current — Continuous	I _C	-600	mA

4. THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Total Device Dissipation, FR-5 Board (Note 1) @ TA = 25°C Derate above 25°C	PD	225 1.8	mW mW/°C
Thermal Resistance, Junction–to–Ambient(Note 1)	R _{θJA}	556	°C/W
Junction and Storage temperature	T _J , T _{stg}	-55~+150	°C

1. FR-5 = 1.0×0.75×0.062 in.

5. ELECTRICAL CHARACTERISTICS (Ta= 25°C)
OFF CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Collector–Emitter Breakdown Voltage (IC = -10 mA, IB = 0)	VBR(CEO)	-60	-	-	V
Collector–Base Breakdown Voltage (IC = -10 μA, IE = 0)	VBR(CBO)	-60	-	-	V
Emitter–Base Breakdown Voltage (IE = -10 μA, IC = 0)	VBR(EBO)	-5	-	-	V
Collector Cutoff Current (VCE = -30V, VBE = -0.5V)	ICEX	-	-	-50	nA
Collector Cutoff Current (VCB = -50 V, IE = 0) (VCB = -50 V, IE = 0, TA = 125°C)	ICBO	-	-	-0.01 -10	μA
Base Cutoff Current (VCE = -30V, VBE = -0.5V)	IBL	-	-	-50	nA

ON CHARACTERISTICS (Note 2.)

DC Current Gain (IC = -0.1 mA, VCE = -10 V) (IC = -1.0 mA, VCE = -10 V) (IC = -10 mA, VCE = -10 V) (IC = -150 mA, VCE = -10 V) (IC = -500 mA, VCE = -10 V)	HFE	75 100 100 100 50	- - - - -	- - - 300 -	
Collector–Emitter Saturation Voltage (IC = -150 mA, IB = -15 mA) (IC = -500 mA, IB = -50 mA)	VCE(sat)	- -	- -	-0.4 -1.6	V
Base–Emitter Saturation Voltage (IC = -150 mA, IB = -15 mA) (IC = -500 mA, IB = -50 mA)	VBE(sat)	- -	- -	-1.3 -2.6	V

SMALL–SIGNAL CHARACTERISTICS





Current–Gain — Bandwidth Product (IC = -50mA, VCE= -20V, f = 100MHz)	fT	200	-	-	MHz
Output Capacitance (VCB = -10 V, IE = 0, f = 1.0 MHz)	Cobo	-	-	8	pF
Input Capacitance (VEB = -2 V, IC = 0, f = 1.0 MHz)	Cibo	-	-	30	pF

SWITCHING CHARACTERISTICS



Turn–On Time	(VCC = -30 V, IC = -150 mA, IB1 = -15 mA)	ton	-	-	45	ns
Delay Time		td	-	-	10	
Rise Time		tr	-	-	40	
Storage Time	(VCC = -6 V, IC = -150 mA, IB1 = IB2 = -15 mA)	ts	-	-	225	
Fall Time		tf	-	-	60	
Turn–Off Time		toff	-	-	280	

2.Pulse Test: Pulse Width ≤300 μs, Duty Cycle ≤2.0%.

6. ELECTRICAL CHARACTERISTICS CURVES




6. ELECTRICAL CHARACTERISTICS CURVES(Con.)



7. OUTLINE AND DIMENSIONS


Notes:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.



DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.89	1	1.11	0.035	0.04	0.044
A1	0.01	0.06	0.1	0.001	0.002	0.004
b	0.37	0.44	0.5	0.015	0.018	0.02
c	0.09	0.13	0.18	0.003	0.005	0.007
D	2.80	2.9	3.04	0.11	0.114	0.12
E	1.20	1.3	1.4	0.047	0.051	0.055
e	1.78	1.9	2.04	0.07	0.075	0.081
L	0.10	0.2	0.3	0.004	0.008	0.012
L1	0.35	0.54	0.69	0.014	0.021	0.029
HE	2.10	2.4	2.64	0.083	0.094	0.104
θ	0°	---	10°	0°	---	10°

8. SOLDERING FOOTPRINT



单击下面可查看定价，库存，交付和生命周期等信息

[>>LRC\(乐山无线电\)](#)