



LMUN5332DW1T1G

S-LMUN5332DW1T1G

Dual Bias Resistor Transistors
NPN and PNP Silicon Surface Mount Transistors
with Monolithic Bias Resistor Network



1. FEATURES

- Simplifies circuit design
- Reduces board space.
- Reduces Component Count
- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.

2. DEVICE MARKING AND RESISTOR VALUES

Device	Marking	R1(K)	R2(K)	Vin(V)Q2	Vin(V)Q1	Shipping
LMUN5332DW1T1G	32	4.7	4.7	-10+30	-30~+10	3000/Tape&Reel
LMUN5332DW1T3G	32	4.7	4.7	-10+30	-30~+10	10000/Tape&Reel

3. MAXIMUM RATINGS(Ta = 25°C)

Parameter	Symbol	Limits	Unit
Collector–Emitter Voltage	V _{CEO}	50	V
Collector–Base Voltage	V _{CBO}	50	V
Collector Current — Continuous	I _C	100	mA

4. THERMAL CHARACTERISTICS

Parameter (One Junction Heated)	Symbol	Limits	Unit
Total Device Dissipation, (Note 1) @ TA = 25°C	PD	187	mW
Derate above 25°C		1.5	mW/°C
Thermal Resistance, Junction–to–Ambient(Note 1)	R _{θJA}	670	°C/W
Parameter (Both Junctions Heated)	Symbol	Limits	Unit
Total Device Dissipation, (Note 1) @ TA = 25°C	PD	250	mW
Derate above 25°C		2	mW/°C
Thermal Resistance, Junction–to–Ambient(Note 1)	R _{θJA}	493	°C/W
Thermal Resistance, Junction–to–Lead(Note 1)	R _{θJL}	188	°C/W
Junction and Storage temperature	T _J , T _{stg}	-55~+150	°C

1. FR-4 @ Minimum Pad

5. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

OFF CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Collector–Emitter Breakdown Voltage (IC = 2.0 mA, IB = 0)	VBR(CEO)	50	-	-	V
Collector–Base Breakdown Voltage (IC = 10 μA, IE = 0)	VBR(CBO)	50	-	-	V
Collector-Base Cutoff Current (VCB = 50 V, IE = 0)	ICBO	-	-	100	nA
Collector-Emitter Cutoff Current (VCE = 50 V, IB = 0)	ICEO	-	-	500	nA
Emitter-Base Cutoff Current (VEB = 6.0 V, IC = 0)	IEBO	-	-	1.5	mA

ON CHARACTERISTICS (Note 2.)


DC Current Gain (IC = 5.0 mA, VCE = 10 V)	HFE	15	30	-	
Collector–Emitter Saturation Voltage (IC = 10 mA, IB = 1 mA)	VCE(sat)	-	-	0.25	V
On-State Input Voltage (VCE=0.3V, IC=20mA)(NPN) (VCE=-0.3V, IC=-20mA)(PNP)	VI(on)	3 -3	- -	- -	V
Off-State Input Voltage (VCE=5V, IC=0.1mA)(NPN) (VCE=-5V, IC=-0.1mA)(PNP)	VI(off)	- -	- -	0.5 -0.5	V
Output Voltage (on) (VCC = 5.0 V, VB = 2.5 V, RL =1.0KΩ)	VOL	-	-	0.2	V
Output Voltage (off) (VCC = 5.0 V, VB = 0.5 V, RL =1.0KΩ)	VOH	4.9	-	-	V
Input Resistor	R1	3.3	4.7	6.1	KΩ
Resistor Ratio	R1/R2	0.8	1.0	1.2	

2. Pulse Test: Pulse Width < 300 μs, Duty Cycle < 2.0%

6. OUTLINE AND DIMENSIONS


Notes:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.



DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	---	---	1.10	---	---	0.043
A1	0.00	---	0.10	0	---	0.004
A2	0.70	0.90	1.00	0.027	0.035	0.039
b	0.15	0.20	0.25	0.006	0.008	0.01
C	0.08	0.15	0.22	0.003	0.006	0.009
D	1.80	2.00	2.20	0.07	0.078	0.086
E	2.00	2.10	2.20	0.078	0.082	0.086
E1	1.15	1.25	1.35	0.045	0.049	0.053
e	0.65 BSC			0.026 BSC		
L	0.26	0.36	0.46	0.010	0.014	0.018
L2	0.15 BSC			0.006 BSC		
aaa	0.15			0.01		
bbb	0.30			0.01		
ccc	0.10			0.00		
ddd	0.10			0.00		

7. SOLDERING FOOTPRINT



DISCLAIMER

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Project, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.

单击下面可查看定价，库存，交付和生命周期等信息

[>>LRC\(乐山无线电\)](#)