

# S-LP48N04D2

## 40V P-Channel Power MOSFET

### 1. FEATURES

- Low thermal impedance.
- Fast switching speed.
- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S-prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.

### 2. APPLICATIONS

- Load switch

### 3. DEVICE MARKING AND RESISTOR VALUES

Device	Marking	Shipping
S-LP48N04D2	48N04	2500pcs/Tape&Reel

### 4. MAXIMUM RATINGS




Parameter		Symbol	Limits	Unit
Drain-to-Source Voltage		VDS	-40	V
Gate-to-Source Voltage		VGS	± 20	V
Continuous Drain Current(Note 1)	TC=25°C	ID	-48	A
	TC=100°C		-30	
Pulsed Drain Current (Note 2)		IDM	-192	A
Avalanche Current		IAS	27.6	A
Avalanche Energy(L=0.1mH)		EAS	38	mJ
Power Dissipation(Note 1)	TC=25°C	PD	50	W
	TC=100°C		20	
Operating Junction and Storage Temperature Range		Tj/Tstg	-55~+150	°C

### 5. THERMAL CHARACTERISTICS

Parameter	Symbol	Max	Unit
Junction-to-Ambient	RθJA	50	°C/W
Junction-to-Case(Note 1)	RθJC	2.5	

Note:1.Surface mounted on "1.5in x 1.5in" FR4 board using 1\*1 in pad, 2 oz Cu.

2.Pulse width limited by maximum junction temperature.







**6. ELECTRICAL CHARACTERISTICS (Ta= 25°C)**





Characteristic	Symbol	Min.	Typ.	Max.	Unit
<b>Static</b>					
Drain–Source Breakdown Voltage (VGS = 0 V, ID = -250 μA)	V(BR)DSS	-40	-	-	V
Zero Gate Voltage Drain Current (VDS= -32 V, VGS= 0 V)	IDSS	-	-	-1	μA
Gate–Body Leakage Current (VDS = 0 V, VGS = ± 20 V)	IGSS	-	-	±100	nA
Gate Threshold Voltage (VDS = VGS, ID = -250 μA)	VGS(th)	-1	-	-2.5	V
Static Drain–Source On–State Resistance(Note 3) (VGS = -10 V, ID = -8 A) (VGS = -4.5 V, ID = -6 A)	RDS(on)	-	-	14 22	mΩ
Diode Forward Voltage (VGS = 0 V, IS = -1 A)	VSD	-	-	-1.2	V
<b>Dynamic</b>					
Input Capacitance	(VDS = -15 V, VGS = 0 V, f = 1MHz)	Ciss	-	3252	-
Output Capacitance		Coss	-	251	-
Reverse Transfer Capacitance		Crss	-	202	-
Total Gate Charge	(VDS = -15 V, VGS = -4.5 V, ID = -6 A)	Qg	-	24.5	-
Gate–Source Charge		Qgs	-	6.7	-
Gate–Drain Charge		Qgd	-	8	-
Turn-On Delay Time	(VDD= -15 V, RL = 15 Ω, ID = -1 A, VGEN = -10 V, RG = 6 Ω)	td(on)	-	16	-
Rise Time		tr	-	9.5	-
Turn-Off Delay Time		td(off)	-	138	-
Fall Time		tf	-	45	-
Gate Resistance (VDS = 0 V, VGS = 0 V, f = 1.0MHz)	Rg	-	4	-	Ω

3. Pulse test: PW ≤ 300us duty cycle ≤ 2%.



### 7. ELECTRICAL CHARACTERISTICS CURVES




**7. ELECTRICAL CHARACTERISTICS CURVES(Con.)**




**7. ELECTRICAL CHARACTERISTICS CURVES(Con.)**




### 8. OUTLINE AND DIMENSIONS



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	2.15	2.30	2.45
A1	0	-	0.20
A2	0.90	1.07	1.17
B	0.68	0.78	0.88
B2	5.20	5.33	5.46
C	0.49	-	0.58
D	5.90	6.10	6.30
D1	5.30REF		
E	6.40	6.60	6.80
E1	4.63	4.83	5.03
e	2.286BSC		
H	9.8	10.10	10.4
L	1.09	1.29	1.49
L1	2.90REF		
L3	0.88	1.08	1.28
L4	0.55	0.80	1.05



### 9. SOLDERING FOOTPRINT



DIM	MIN(mm)
A	6.03
A1	4.50
A2	6.46
A3	4.10
A4	2.37
B	6.50
C	2.50
D	1.68
e	4.80
H	12.35
F	5.95

## **DISCLAIMER**

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Porject, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.

单击下面可查看定价，库存，交付和生命周期等信息

[>>LRC\(乐山无线电\)](#)