

# LESD5L5.0CT1G

## Transient Voltage Suppressors

### ESD Protection Diodes with Ultra-Low Capacitance

The ESD5L is designed to protect voltage sensitive components that require ultra-low capacitance from ESD and transient voltage events. Excellent clamping capability, low capacitance, low leakage, and fast response time, make these parts ideal for ESD protection on designs where board space is at a premium. Because of its low capacitance, it is suited for use in high frequency designs such as USB 2.0 high speed and antenna line applications.

#### Specification Features:

- Ultra Low Capacitance 0.5 pF
- Low Clamping Voltage
- Small Body Outline Dimensions:  
0.047" x 0.032" (1.20 mm x 0.80 mm)
- Low Body Height: 0.016" (0.4 mm)
- Stand-off Voltage: 5 V
- Low Leakage
- Response Time is Typically < 1.0 ns
- IEC61000-4-2 Level 4 ESD Protection
- This is a Pb-Free Device

#### Mechanical Characteristics:

**CASE:** Void-free, transfer-molded, thermosetting plastic  
Epoxy Meets UL 94 V-0

**LEAD FINISH:** 100% Matte Sn (Tin)

**QUALIFIED MAX REFLOW TEMPERATURE:** 260°C

Device Meets MSL 1 Requirements


#### MAXIMUM RATINGS

| Rating                                                                    | Symbol           | Value       | Unit |
|---------------------------------------------------------------------------|------------------|-------------|------|
| IEC 61000-4-2 (ESD)<br>Contact<br>Air                                     |                  | ±10<br>±15  | kV   |
| Total Power Dissipation on FR-5 Board<br>(Note 1) @ T <sub>A</sub> = 25°C | P <sub>D</sub>   | 200         | mW   |
| Peak Pulse Power (tp= 8/20us)                                             | P <sub>PP</sub>  | 100         | W    |
| Storage Temperature Range                                                 | T <sub>stg</sub> | -55 to +150 | °C   |
| Junction Temperature Range                                                | T <sub>J</sub>   | -55 to +125 | °C   |
| Lead Solder Temperature - Maximum<br>(10 Second Duration)                 | T <sub>L</sub>   | 260         | °C   |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. FR-5 = 1.0 x 0.75 x 0.62 in.

# LESD5L5.0CT1G



#### Ordering information


| Device        | Marking | Shipping       |
|---------------|---------|----------------|
| LESD5L5.0CT1G | L5      | 3000/Tape&Reel |

# LESD5L5.0CT1G

## ELECTRICAL CHARACTERISTICS

(T<sub>A</sub> = 25°C unless otherwise noted)


| Symbol           | Parameter                                          |
|------------------|----------------------------------------------------|
| I <sub>PP</sub>  | Maximum Reverse Peak Pulse Current                 |
| V <sub>C</sub>   | Clamping Voltage @ I <sub>PP</sub>                 |
| V <sub>RWM</sub> | Working Peak Reverse Voltage                       |
| I <sub>R</sub>   | Maximum Reverse Leakage Current @ V <sub>RWM</sub> |
| V <sub>BR</sub>  | Breakdown Voltage @ I <sub>T</sub>                 |
| I <sub>T</sub>   | Test Current                                       |
| I <sub>F</sub>   | Forward Current                                    |
| V <sub>F</sub>   | Forward Voltage @ I <sub>F</sub>                   |
| P <sub>pk</sub>  | Peak Power Dissipation                             |
| C                | Capacitance @ V <sub>R</sub> = 0 and f = 1.0 MHz   |




## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

| Device        | Device Marking | V <sub>RWM</sub> (V) | I <sub>R</sub> (μA) @ V <sub>RWM</sub> | V <sub>BR</sub> (V) @ I <sub>T</sub> (Note 2) | I <sub>T</sub> (mA) | C (pF) |     | V <sub>C</sub> (V) @ I <sub>PP</sub> = 1 A (Note 3) | V <sub>C</sub> Per IEC61000-4-2 (Note 4) |
|---------------|----------------|----------------------|----------------------------------------|-----------------------------------------------|---------------------|--------|-----|-----------------------------------------------------|------------------------------------------|
|               |                | Max                  | Max                                    | Min                                           |                     | Typ    | Max | Max                                                 |                                          |
| LESD5L5.0CT1G | L5             | 5.0                  | 1.0                                    | 5.4                                           | 1.0                 | 0.5    | 0.9 | 12.9                                                | Figures 1 and 2 See Below                |

- V<sub>BR</sub> is measured with a pulse test current I<sub>T</sub> at an ambient temperature of 25°C.
- Surge current waveform per Figure 5.
- For test procedure see Figures 3 and 4.



**Figure 1. ESD Clamping Voltage Screenshot Positive 8 kV Contact per IEC61000-4-2**



**Figure 2. ESD Clamping Voltage Screenshot Negative 8 kV Contact per IEC61000-4-2**

# LESD5L5.0CT1G

IEC 61000-4-2 Spec.

| Level | Test Voltage (kV) | First Peak Current (A) | Current at 30 ns (A) | Current at 60 ns (A) |
|-------|-------------------|------------------------|----------------------|----------------------|
| 1     | 2                 | 7.5                    | 4                    | 2                    |
| 2     | 4                 | 15                     | 8                    | 4                    |
| 3     | 6                 | 22.5                   | 12                   | 6                    |
| 4     | 8                 | 30                     | 16                   | 8                    |

IEC61000-4-2 Waveform




Figure 3. IEC61000-4-2 Spec




Figure 4. Diagram of ESD Test Setup





Figure 5. 8 X 20  $\mu\text{s}$  Pulse Waveform


# LESD5L5.0CT1G

## SOD-523




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: MILLIMETER.
  3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

| DIM | MILLIMETERS |      |      | INCHES |        |        |
|-----|-------------|------|------|--------|--------|--------|
|     | MIN         | NOM  | MAX  | MIN    | NOM    | MAX    |
| A   | 1.10        | 1.20 | 1.30 | 0.043  | 0.047  | 0.051  |
| B   | 0.70        | 0.80 | 0.90 | 0.028  | 0.032  | 0.035  |
| C   | 0.50        | 0.60 | 0.70 | 0.020  | 0.024  | 0.028  |
| D   | 0.25        | 0.30 | 0.35 | 0.010  | 0.012  | 0.014  |
| J   | 0.07        | 0.14 | 0.20 | 0.0028 | 0.0055 | 0.0079 |
| K   | 0.15        | 0.20 | 0.25 | 0.006  | 0.008  | 0.010  |
| S   | 1.50        | 1.60 | 1.70 | 0.059  | 0.063  | 0.067  |



### SOLDERING FOOTPRINT\*



单击下面可查看定价，库存，交付和生命周期等信息

[>>LRC\(乐山无线电\)](#)

[>>点击查看相关商品](#)