


LTVS20H7.0T5G

LTVS20H7.0T5G

Features

- 7V uni-directional ESD diode
- Low clamping voltage
- Complies with IEC 61000-4-2 standards:
 - Air discharge: $\pm 30\text{kV}$
 - Contact discharge: $\pm 30\text{kV}$
- RoHS Compliant



DFN2020-3



Ordering information

Device	Marking	Packing
LTVS20H7.0T5G	C2	DFN2020-3

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	Ppk	2800	W
Peak Pulse Current (8/20 μs)	I _{PP}	165	A
Operating Temperature Range	T _J	-55 to +125	$^\circ\text{C}$
Storage Temperature Range	T _{stg}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V _{RWM}			7.0	V	
Breakdown Voltage	V _{BR}	7.6		9	V	I _T = 1mA
Reverse Leakage Current	I _R			2	μA	V _R = 7.0V
Clamping Voltage	V _C			10	V	I _{PP} = 60A (8 x 20 μs pulse)
Clamping Voltage	V _C			17	V	I _{PP} = 165A (8 x 20 μs pulse)
Forward Voltage	V _F		0.75	1.2	V	I _F = 10mA

Note: Electrical parameters are only for die, performance may alter after assembly.

LTVS20H7.0T5G

Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)




Fig 1. Clamping Voltage vs. Peak Pulse Current




Fig 2. 8 X 20uS Pulse Waveform




Fig 3 . ESD Clamping Voltage
Positive 8 kV Contact per IEC61000-4-2





Fig 4 . ESD Clamping Voltage
Negative 8 kV Contact per IEC61000-4-2

LTVS20H7.0T5G

OUTLINE AND DIMENSIONS


DFN2020-3



DFN2020-3			
Dim	Min.	Typ.	Max.
A	0.60	0.65	0.70
A1	0.00	0.02	0.05
A3	0.152REF.		
D	1.95	2.00	2.05
E	1.95	2.00	2.05
D1	1.45	1.50	1.55
E1	0.95	1.00	1.05
b	0.25	0.30	0.35
e	1.30TYP.		
k	0.20	0.25	0.30
L	0.35	0.40	0.45
All Dimensions in mm			

SOLDERING FOOTPRINT

DFN2020-3



DFN2020-3	
Dim	(mm)
X	1.60
Y	2.00
b1	0.35
b2	0.45
L	0.50
Y1	1.10
k	0.15
e	1.30

单击下面可查看定价，库存，交付和生命周期等信息

[>>LRC\(乐山无线电\)](#)

[>>点击查看相关商品](#)