

**Features**

- Low  $R_{DS(on)}$  & FOM
- Extremely Low Switching Loss
- Excellent Stability and Uniformity
- Fast Switching and Soft Recovery
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

**Maximum Ratings**


- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 62°C/W Junction to Ambient<sup>(1)</sup>
- Thermal Resistance: 0.65°C/W Junction to Case

Parameter	Symbol	Value
Drain-Source Voltage	$V_{DS}$	100V
Gate-Source Voltage	$V_{GS}$	±20V
Continuous Drain Current <sup>(2)</sup> , $T_C=25^\circ C$	$I_D$	130A
Pulsed Drain Current <sup>(3)</sup> , $T_C=25^\circ C$	$I_{D,pluse}$	390A
Power Dissipation <sup>(4)</sup> , $T_C=25^\circ C$	$P_D$	192W
Single Pulsed Avalanche Energy <sup>(5)</sup>	$E_{AS}$	500mJ


**Note:**

1. The Value of  $R_{\theta JA}$  is Measured with the Device Mounted on 1 in<sup>2</sup> FR-4 Board with 2oz. Copper, In a Still Air Environment with  $T_A=25^\circ C$ .
2. Calculated Continuous Current Based on Maximum Allowable Junction Temperature.
3. Repetitive Rating: Pulse Width Limited By Max. Junction Temperature.
4.  $P_d$  is Based on Max. Junction Temperature, Using Junction-Case Thermal Resistance.
5.  $V_{DD}=50V$ ,  $R_G=25\Omega$ ,  $L=0.5mH$ , Starting  $T_J=25^\circ C$ .

**Internal Structure and Marking Code**




1. Gate
- 2,4. Drain
3. Source



YWWTT: 5 codes in total  
Y is the year  
WW is the cycle  
TT is the line type


**N-Channel MOSFET**

**D2-PAK**



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.331	0.370	8.40	9.40	
B	0.378	0.417	9.60	10.60	
C	0.165	0.189	4.20	4.80	
D	0.027	0.037	0.68	0.94	
E	0.045	0.055	1.14	1.40	
G	0.010		2.54		TYP.
H	0.096	0.134	2.43	3.40	
J	0.011	0.025	0.28	0.64	
K	0.071	0.131	1.80	3.32	
S	0.575	0.625	14.60	15.87	
V	0.042	0.058	1.07	1.47	
W	0.000	0.010	0.00	0.25	

**Suggested Solder Pad Layout**



Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
<b>Static Characteristics</b>							
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	100			V	
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1.2	2	4	V	
Gate-Body Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 20V$			$\pm 100$	nA	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=100V, V_{GS}=0V$			1	$\mu A$	
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=60A$		4.0	4.6	m $\Omega$	
<b>Dynamic Characteristics</b>							
Drain-Source On-Voltage	$C_{ISS}$	$V_{GS}=0V, V_{DS}=50V, f=1MHz$		6124.6		pF	
Output Capacitance	$C_{OSS}$			792.3		pF	
Reverse Transfer Capacitance	$C_{RSS}$			15.1		pF	
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V, V_{DS}=50V, R_G=2.2\Omega, I_D=22A$		28.2		ns	
Rise Time	$t_r$			7.5		ns	
Turn-Off Delay Time	$t_{d(off)}$			81.9		ns	
Fall Time	$t_f$			20.1		ns	
<b>Gate Charge Characteristics</b>							
Total Gate Charge	$Q_g$	$I_D=22A, V_{DS}=50V, V_{GS}=10V$		101.6		nC	
Gate-Source Charge	$Q_{gs}$			20.6		nC	
Gate-Drain Charge	$Q_{gd}$			28.7		nC	
Gate Plateau Voltage	$V_{plateau}$			4.2		V	
<b>Body Diode Characteristics</b>							
Diode Forward Current	$I_S$	$V_{GS}<V_{th}$			130	A	
Pulsed Source Current	$I_{SP}$				390	A	
Diode Forward Voltage	$V_{SD}$	$I_S=20A, V_{GS}=0V$			1.3	V	
Reverse Recovery Time	$t_{rr}$	$I_S=10A, di/dt=100A/\mu s$		82.1		ns	
Reverse Recovery Charge	$Q_{rr}$				248.4		nC
Peak Reverse Recovery Current	$I_{rrm}$				4.9		A

**Curve Characteristics**

Fig. 1 - Typical Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 - Capacitance Characteristics




Fig. 4 - Total Gate Charge Characteristics




Fig. 5 -  $I_s - V_{SD}$





Fig. 6 - On-Resistance Characteristics



## Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 800pcs/Reel
Part Number-BP	Tube: 5Kpcs/Ctn

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp** . products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MCC\(美微科\)](#)