


Features

- Halogen Free. "Green" Device (Note 1)
- Lead Free Finish/RoHS Compliant (Note2) ("P"Suffix Designates Compliant. See Ordering Information)
- Ultra Fast Switching For High Efficiency
- For Surface Mounted Applications
- High Current Capability
- Low Reverse Leakage Current
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +175°C
- Maximum Thermal Resistance: 16 °C/W Junction to Lead

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MURS3JAFL	UR3J	600V	420V	600V



Average Forward Current	I _{F(AV)}	3.0A	T _L =75⁰C
Peak Forward Surge Current	I _{FSM}	100A	8.3ms,Half Sine
Maximum Instantaneous Forward Voltage	V_{F}	1.7V	I _{FM} =3.0A; T _J =25⁰C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	5.0µA	TJ=22₀C
Maximum Reverse Recovery Time	t _{rr}	35ns	I _F =0.5A; I _R =1.0A; I _{RR} =0.25A
Typical Junction Capacitance	CJ	45pF	Measured at 1.0MHz, V _R =4.0V


Note:

1. Halogen free "Green" products are defined as those which contain <900ppm bromine,

<900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.</p>
2. High Temperature Solder Exemptions Applied, See EU Directive Annex Notes 7a.


3.0 Amp Super Fast Rectifiers 600 Volts


DO-221AC(SMA-FL)



DIMENSIONS						
DIM	INCHES		MM		NOTE	
	MIN	MAX	MIN	MAX	NOTE	
А	0.035	0.049	0.90	1.25		
В	0.049	0.065	1.25	1.65		
С	0.004	0.016	0.10	0.40		
D	0.089	0.116	2.25	2.95		
E	0.173	0.220	4.40	5.60		
E1	0.126	0.181	3.20	4.60		
L	0.020	0.059	0.50	1.50		


SUGGESTED SOLDER PAD LAYOUT










Curve Characteristics











Ordering Information

Device	Packing		
Part Number-TP	Tape&Reel: 10Kpcs/Reel		

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp*. products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价,库存,交付和生命周期等信息

>>MCC(美微科)