

### Features

- Low Leakage
- High Surge Current Capability
- Epoxy Meets UL 94 V-0 Flammability Rating
- Glass Passivated Junction
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix Designates
- Compliant. See Ordering Information)

# **Maximum Ratings**


- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Typical Thermal Resistance: 12°C/W Junction to Ambient


MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
6A05G	6A05G	50V	35V	50V
6A1G	6A1G	100V	70V	100V
6A2G	6A2G	200V	140V	200V
6A4G	6A4G	400V	280V	400V
6A6G	6A6G	600V	420V	600V
6A8G	6A8G	800V	560V	800V
6A10G	6A10G	1000V	700V	1000V

## Electrical Characteristics @ 25°C Unless Otherwise Specifie

Average Forward Current	I <sub>F(AV)</sub>	6.0A	T <sub>A</sub> =75⁰C
Peak Forward Surge Current	I <sub>FSM</sub>	200A 400A	8.3ms,Half Sine Wave 1.0ms,Square Wave
Maximum Instantaneous Forward Voltage	V <sub>F</sub>	1.0V	I <sub>FM</sub> =6.0A;
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	10µА 50µА	T <sub>J</sub> =25°C T <sub>J</sub> =100°C
Typical Junction Capacitance	CJ	100pF	Measured at 1.0MHz, V <sub>R</sub> =4.0V

Note :1. High Temperature Solder Exemption Applied, See EU Directive Annex 7a.







## **Curve Characteristics**








Fig. 3 - Typical Instantaneous Forward Characteristics











### **Ordering Information**

Device	Packing
Part Number-TP	Tape&Reel: 500pcs/Reel
Part Number-AP	Ammo Packing: 450pcs/Ammo Box
Part Number-BP	Bulk: 200pcs/Box ;4.8Kpcs/Carton

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp*. products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价,库存,交付和生命周期等信息

>>MCC(美微科)