

Features

- · Low Clamping Voltage
- · Ultra Low Capacitance
- · Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free. "Green" Device (Note 1)
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C

MCC Part Number	Device Marking		
ESDSLC5V0L2B	5N		

IEC61000-4-2(ESD)	Air Contact	±20KV ±20KV
IEC61000-4-4 (EFT) @5/50ns		40A
Peak Pulse Current(8/20μs)	I _{PP}	3A
Peak Pulse Power (8/20µs)	P _{PK}	40W


Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

Internal Structure



ESD Protection Device


DFN1006-2L



	DIMENSIONS					
DIM	INCHES		MM		NOTE	
Dilvi	MIN	MAX	MIN	MAX	NOTE	
Α	0.037	0.041	0.95	1.05		
В	0.022	0.026	0.55	0.65		
С	0.016	0.020	0.40	0.50		
C1		0.002		0.05		
D	0.001	0.003	0.02	0.08		
Е	0.026		0.65		TYP.	
F	0.008	0.012	0.20	0.30		
G	0.018	0.022	0.45	0.55		



ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)





Electrical Characteristics @ 25°C (Unless Otherwise Specified)


Parameter	Symbol	Conditions	Min.	Тур.	Max.	Units
Reverse Working Voltage	V _{RWM}				5.5	V
Trigger Voltage	V_{TRIG}	High Voltage than V _{TRIG} Guarantees the Protection Turn-On	6.5			V
Holding Voltage	V _H	I _H =1mA,Lower Voltage than V _{TRIG} Guarantees the Protection Turn-Off	6.1	7	8.8	V
Reverse Leakage Current	I _R	V _{RWM} =5.5V			50	nA
Clamping Voltage	V _C	I _{PP} =1A, t _P =8/20μs			13	V
Clamping Voltage	V _C	I _{PP} =3A, t _P =8/20μs			15	V
Junction Capacitance	CJ	$V_R = 0V$, $f = 1MHz$		0.15	0.2	pF





Curve Characteristics













Ordering Information

Device	Packing		
Part Number-TP	Tape&Reel: 10Kpcs/Reel		

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp**, products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Rev.3-3-12012020 ______ MCCSEMI.COM

单击下面可查看定价,库存,交付和生命周期等信息

>>MCC(美微科)