

## ۶Ľ

E502650

## Features

- Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix Designates Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating
- High Conductivity Metal Case

## **Maximum Ratings**

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 3.0°C/W Junction to Case

## **Mechanical Data**

- Mounting Torque: 10 Kg·cm Maximum
- Mounting Hole For #8 Screw


MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MP3505W	MP3505W	50V	35V	50V
MP351W	MP351W	100V	70V	100V
MP352W	MP352W	200V	140V	200V
MP354W	MP354W	400V	280V	400V
MP356W	MP356W	600V	420V	600V
MP358W	MP358W	800V	560V	800V
MP3510W	MP3510W	1000V	700V	1000V

## Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I <sub>F(AV)</sub>	35.0A	T <sub>C</sub> = 55°C
Peak Forward Surge Current	I <sub>FSM</sub>	400A	8.3ms, Half Sine
Maximum Forward Voltage Drop Per Element	V <sub>F</sub>	1.1V	I <sub>FM</sub> = 17.5A; T <sub>J</sub> = 25°C
Maximum DC Reverse Current at Rated DC Blocking Voltage	I <sub>R</sub>	5µA 500µA	T <sub>J</sub> = 25°C T <sub>J</sub> = 125°C
Rating for Fusing	l²t	660A <sup>2</sup> s	t<8.3ms

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7a.


# 35 Amp Single Phase Bridge Rectifier 50 to 1000 Volts









## **Curve Characteristics**











Fig. 4 - Typical Reverse Leakage Characteristics







## **Ordering Information**

Device	Packing
Part Number-BP	Bulk: 50Úcs/Box, 400Pcs/Ctn

#### \*\*\*IMPORTANT NOTICE\*\*\*

*Micro Commercial Components Corp*. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp*. products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

## \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价,库存,交付和生命周期等信息

>>MCC(美微科)