

Features

- Internal Thermal Overload Protection
- Low Dropout Voltage: 1.15V(typ.) at 800mA Output Current
- Moisture Sensitivity Level 3
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free. "Green" Device (Note 1)
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)

Maximum Ratings

- Thermal Resistance: 100°C/W Junction to Ambient
- Storage Temperature Range: -55°C to +150°C
- Operating Junction Temperature : 150°C

Parameter	Symbol	Value	Unit
Input Voltage	V_I	20	V
ESD Voltage (Machine Model)	V_{ESD}	400	V


Recommended Operating Conditions

Parameter	Symbol	Value	Unit
Input Voltage	V_I	15	V
Operating Junction Temperature	T_j	-25 ~125	°C

Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

Low Dropout Linear Regulator


SOT-89



DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.169	0.185	4.30	4.70	
B	0.061		1.55		TYP.
C	0.154	0.171	3.91	4.35	
D	0.031	0.047	0.80	1.20	
E	0.089	0.104	2.25	2.65	
F	0.118		3.00		TYP.
G	0.013	0.020	0.33	0.52	
H	0.015	0.021	0.38	0.53	
J	0.014	0.017	0.35	0.44	
K	0.055	0.063	1.40	1.60	
L	0.059		1.50		TYP.

Suggested Solder Pad Layout



Electrical Characteristics (T_a=25 °C Unless Otherwise Specified)

Parameter	Symbol	Part Number	Test Conditions	Min	Typ	Max	Unit
Reference Voltage	V _{ref}	MCA1117C-ADJ	10mA ≤ I _{out} ≤ 800mA, V _{in} =3.25V	1.225	1.25	1.275	V
Output Voltage	V _{out}	MCA1117C-1.2	0 ≤ I _{out} ≤ 800mA, V _{in} =3.2V	1.176	1.2	1.224	V
		MCA1117C-1.8	0 ≤ I _{out} ≤ 800mA, V _{in} =3.8V	1.764	1.8	1.836	V
		MCA1117C-2.5	0 ≤ I _{out} ≤ 800mA, V _{in} =4.5V	2.45	2.5	2.55	V
		MCA1117C-2.85	0 ≤ I _{out} ≤ 800mA, V _{in} =4.85V	2.793	2.85	2.907	V
		MCA1117C-3.3	0 ≤ I _{out} ≤ 800mA, V _{in} =5.3V	3.234	3.3	3.366	V
		MCA1117C-5.0	0 ≤ I _{out} ≤ 800mA, V _{in} =7.0V	4.9	5	5.1	V
Line Regulation	ΔV _{out}	MCA1117C-1.2	I _{out} =10mA, 2.7V ≤ V _{in} ≤ 10V	-	0.03	0.2	%/V
		MCA1117C-ADJ	I _{out} =10mA, 2.75V ≤ V _{in} ≤ 12V	-	0.03	0.2	%/V
		MCA1117C-1.8	I _{out} =10mA, 3.3V ≤ V _{in} ≤ 12V	-	0.03	0.2	%/V
		MCA1117C-2.5	I _{out} =10mA, 4.0V ≤ V _{in} ≤ 12V	-	0.03	0.2	%/V
		MCA1117C-2.85	I _{out} =10mA, 4.35V ≤ V _{in} ≤ 12V	-	0.03	0.2	%/V
		MCA1117C-3.3	I _{out} =10mA, 4.8V ≤ V _{in} ≤ 12V	-	0.03	0.2	%/V
		MCA1117C-5.0	I _{out} =10mA, 6.5V ≤ V _{in} ≤ 12V	-	0.03	0.2	%/V
Load Regulation	ΔV _o	MCA1117C-1.2	V _{in} = 2.7V, 10mA ≤ I _{out} ≤ 800mA	-	2	8	mV
		MCA1117C-ADJ	V _{in} = 2.75V, 10mA ≤ I _{out} ≤ 800mA	-	2	8	mV
		MCA1117C-1.8	V _{in} = 3.3V, 10mA ≤ I _{out} ≤ 800mA	-	3	12	mV
		MCA1117C-2.5	V _{in} = 4.0V, 10mA ≤ I _{out} ≤ 800mA	-	4	16	mV
		MCA1117C-2.85	V _{in} = 4.35V, 10mA ≤ I _{out} ≤ 800mA	-	5	20	mV
		MCA1117C-3.3	V _{in} = 4.8V, 10mA ≤ I _{out} ≤ 800mA	-	6	24	mV
		MCA1117C-5.0	V _{in} = 6.5V, 10mA ≤ I _{out} ≤ 800mA	-	9	36	mV
Dropout Voltage	V _{drop}		I _{out} = 100mA	-	1.2	1.3	V
			I _{out} = 800mA	-	1.3	1.5	V
Minimum Load Current	I _{min}	MCA1117C-ADJ		-	2	10	mA
Quiescent Current	I _q	MCA1117C-1.2	V _{in} =10V	-	2	5	mA
		MCA1117C-1.8	V _{in} =12V	-	2	5	mA
		MCA1117C-2.5	V _{in} =12V	-	2	5	mA
		MCA1117C-2.85	V _{in} =12V	-	2	5	mA
		MCA1117C-3.3	V _{in} =12V	-	2	5	mA
		MCA1117C-5.0	V _{in} =12V	-	2	5	mA
Adjustment Pin Current	I _{adj}	MCA1117C-ADJ	V _{in} =5V, 10mA ≤ I _{out} ≤ 800mA	-	55	120	μA
I _{adj} change	I _{change}	MCA1117C-ADJ	V _{in} =5V, 10mA ≤ I _{out} ≤ 800mA	-	0.2	10	μA
Temperature Coefficient	ΔV/ΔT		V _o =10V F=100Hz, C _{ADJ} =10μF	-	±100	-	ppm

Ordering Information

Device	Packing
Part Number-TP	Tape&Reel:1Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp.* products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MCC\(美微科\)](#)